ONKRON
designed to support

TS2811E-B





Screen size:
50" - 120"

Max load:
125 kg

VESA:
200x200 - 800x600 mm

Height adjustment:
910 mm-1560 mm

Made of	SPCC cold rolled steel
Max. load of monitors/TVs	120 kg
VESA	200x200, 200x300, 200x400, 200x500, 300x200, 300x300, 300x400, 300x500, 400x200, 400x300, 400x400, 400x500, 500x200, 500x400, 500x500, 600x200, 600x300, 600x400, 700x400, 700x500, 800x200, 800x400, 800x500, 800x600, 900x800 mm
Screen size (min)	50"
Screen size (max)	120"
Height adjustment (min)	910 mm
Height adjustment (max)	1560 mm
Travel speed	24 мм/сек mm/s
Remote control range	10 м m
Dimensions of the individual package	114x62x26.5 cm
Individual package volume	1.87 m³
Gross weight individual	49 kg

ONKRON mounting solutions:
· Are suitable for continuous 24/7 use when installed and used in accordance with the applicable product documentation, installation instructions, and load specifications;
· Are intended for professional and commercial installations;
· Are designed to support secure and reliable installation of compatible displays in public environments;
· Comply with standard safety, installation, and mechanical requirements applicable to professional display mounting solutions;
· May be used in high-traffic public spaces, provided that installation is performed by qualified personnel and in accordance with all applicable local regulations, safety standards, and project requirements.

© 2026 Products or images of ONKRON™ are subject to change without notice.