

# Digitus® USB-C 3.2 Gen2 extension cable, USB-C - USB-C

AK-300210-007-S  
EAN 4016032451129



## USB Type-C extension cable, type C M/F, 0.7m, Gen2, 5A, 10GB, 3.2 Version, bl

This USB Type-C extension cable allows you to extend the usage distance of the Type-C interface on your notebook, tablet, smartphone or docking station.

### Extend your original Type-C port on your MacBook or other device to a suitable position

- USB 3.2 data transfer rate up to 10 Gbps, Superspeed+
- Supports power supply up to 20V/5A, 100W
- Supports the USB PD (Power delivery) specification.
- Video/audio support up to 4K (4096x2304, 30Hz)

- Supports DisplayPort video/audio signals

### Attributes

- AWG: 26
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB-C jack
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 3.0 / 3.1
- Length: 0.7 m
- Shielding: Double shielding

| Logistics                    |              |             |            |            |             |           |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
| Packaging Unit Carton        | 200          | 5.90        | 35.00      | 26.00      | 24.00       | 21,840.00 |
| Packaging Unit Inside        | 10           | 0.30        | 25.00      | 30.00      | 7.60        | 5,700.00  |
| Packaging Unit Single        | 1            | 0.03        | 1.00       | 11.50      | 21.50       | 247.25    |
| Net single without Packaging | 1            | 0.03        | 1.00       | 10.50      | 9.00        | 0.00      |

## More images:



## Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable.
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

## EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)