

k0-R1

2-WAY MULTICELLED LOUDSPEAKER



LIMITED EDITION
The Klipsch + OJAS k0-R1 is a strictly limited edition. The unparalleled uniqueness of this product and the innovative collaboration between Klipsch and OJAS have generated demand that exceeds our inventory. Secure your piece of audio history today, before they vanish into history.

LEGENDARY PEDIGREE
Handcrafted in Hope, Arkansas, USA by skilled Klipsch artisans, the k0-R1 exemplifies nearly a century of speaker-building expertise, delivering a meticulously built loudspeaker of unparalleled quality.

BUILT TO STUN
The k0-R1 epitomizes OJAS’s visionary design philosophy, incorporating bespoke materials such as an exposed sandcast aluminum multicell horn and Baltic birch plywood with full butt joint construction. Available in spiral red oak veneer or pewter gray finishes with a matte black horn.

TECH DELIGHTERS
Embodying a minimalist ethos, the k0-R1 features bespoke materials and cutting-edge components, including an adjustable horn mount, anodized aluminum binding posts, and anti-vibration rubber feet. A laser-engraved metal ID plate adds a touch of exclusivity, while a five-step high-frequency gain attenuator provides precise sound tuning.

STANDING OVATION
The limited edition Klipsch / OJAS k0-R1 arrives accompanied by the robust Klipsch KS-12 speaker stands, ensuring the perfect elevation and presentation for these extraordinary loudspeakers.

KEEPSAKE
The k0-R1 comes with a meticulously crafted hardbound book that chronicles the journey of inspiration, research, ideation, design, and manufacturing behind the creation of this exceptional loudspeaker.

SPECIFICATIONS	
FREQUENCY RESPONSE ¹	51 Hz - 20kHz +/- 3dB
FREQUENCY RESPONSE (f10) ¹	40 Hz - 21kHz -10dB
POWER HANDLING ²	200W (28.3V) 40 Hz - 10kHz
CALCULATED MAX. CONTINUOUS OUTPUT ³	117db 40 Hz - 10kHz
SENSITIVITY ⁴	97.5 db @ 2.83V
CROSSOVER POINT	970 Hz
HORIZONTAL COVERAGE PATTERN	90 degrees, +/- 30 degrees, 600Hz to 15kHz
VERTICAL COVERAGE PATTERN	60 degrees, +/- 30 degrees, 2kHz to 15kHz
NOMINAL IMPEDANCE	8 ohm (4.40 ohm min. @ 133 Hz)
TRANSDUCERS	K-28-E 12" Woofer; K-706 HF Driver
ENCLOSURE ⁵	vented system
ENCLOSURE MATERIAL	13-ply Grade A Baltic Birch Plywood
TERMINALS	5 way binding posts
DIMENSIONS	16.5" (42cm) W x 28.125" (71.4cm) H x 13.0" (33cm) D
NET WEIGHT	52 lbs. (23.6kg)
SHIPPING WEIGHT	59 lbs (26.8kg)

¹ 3M, Half-space anechoic
² AES standard, continuous pink noise, 6dB peaks
³ Calculated at 1M half-spaced at power handling power input
⁴ SPL at 1M, half-spaced anechoic with 2.83 volts input

FINISH TYPE	SKU	EAN
HAMMERTONE GREY	1080068	743878092332
FIGUEROA VENEER	1080069	0743878092349