

ProArt Display PA248CRV



Key Features



WUXGA
1920x1200

16:10 1920x1200 resolution
for crystal clear image
quality



IPS technology is optimized
for the finest image quality
with 178° wide-viewing-angle



provides brighter imagery and
supports the cinema-standard
97% DCI-P3 color gamut



International color standard
100% sRGB / 100% Rec. 709
color space for digital
images and video
production



Factory pre-calibrated to
guarantee the ΔE color
difference less than 2



Full function USB-C
connection for DisplayPort
video, USB data transmission
and supports 96W power
delivery



Daisy-chain

DisplayPort allows users to
daisy chain up to 4 monitors
for a multi-display
workstation from one video
source



USB Hub

Embedded four USB ports for
connecting mouse, keyboard,
or other USB devices



4-way Ergonomic
Stand

Ergonomically-designed
stand with tilt, swivel, pivot,
and height adjustments

ASUS

ProArt Display PA248CRV

Spec Sheet

Display	Panel Size : 24.1-inch (61.13cm) Wide Screen (16:10) Display Viewing Area(HxV) : 518.4 x 324.0 mm Display Surface : Non-Glare Panel Type : IPS Viewing Angle (CR≥10, H/V) : 178° / 178° Pixel Pitch : 0.270 mm Resolution : 1920x1200 Color Space (sRGB) : 100% Color Space (Rec. 709) : 100% Color Space (DCI-P3) : 97% Brightness (Typ.) : 350cd/m² Contrast Ratio (Typ.) : 1000:1 Display Colors : 16.7M Response Time : 5ms (GTG) Refresh Rate (Max) : 75Hz HDR (High Dynamic Range) Support : HDR-10 Flicker-free : Yes
Video Feature	ProArt Preset : Native / sRGB / Rec. 709 / DCI-P3 / Adobe RGB / Rec. 2020 / DICOM / HDR / User Mode 1 / User Mode 2 Color Temp. Selection : Yes (5 modes) Color Adjustment : 6-axis adjustment (R,G,B,C,M,Y) Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes QuickFit Plus : Yes HDCP : Yes, 1.4 VRR Technology : Adaptive-Sync (48~75Hz) Low Blue Light : Yes
Audio Feature	Speaker : Yes (2Wx2)
IO ports	USB-C x 1 DisplayPort 1.4 x 2 (Daisy Chain) HDMI(v1.4) x 2 USB-C Power Delivery : 96W USB Hub : Yes (USB 3.2 Gen 1 Type-C; USB 3.2 Gen 1 Type-A x 3) Earphone Jack : Yes Diagram labels: DisplayPort1.4, DisplayPort1.4 (MST), Earphone Jack, USB Hub, HDMI (v1.4), Full Function USB-C
Signal Frequency	Digital Signal Frequency : USB-C, DisplayPort : 95~95 KHz (H) / 48~75 Hz (V) HDMI : 30~95 KHz (H) / 48~75 Hz (V)
Power Consumption	Power On (Typical): < 9W Power Saving Mode : < 0.5W ; Power Off Mode : 0W (Hard Switch) 100~240V, 50/60Hz
Mechanical Design	Tilt : Yes (+23° ~ -5°) Swivel : Yes (+30° ~ -30°) Pivot : 90° (Clockwise& Anticlockwise) Height Adjustment : 0~130mm VESA Wall Mounting : 100x100mm Kensington Lock : Yes
Dimensions (Est.)	Phys. Dimension with Stand (W x H x D) : 531.69 x (399.2~529.2) x 190.37 mm Phys. Dimension without Stand (W x H x D) : 531.69 x 350.18 x 44.1 mm Box Dimension (W x H x D) : 610 x 414 x 126 mm
Weight (Est.)	Net Weight with Stand : 5.91 Kg Net Weight without Stand : 4.2 Kg Gross Weight : 8.39 Kg
Accessories	Power cord, USB-C cable (optional), HDMI cable (optional), DisplayPort cable (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card
Compliance Standard	FCC, cTUVus, ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, e-Standby, PSB, VN MEPS, Energy Star, TCO, RoHS, CEC, WHQL Windows 10/11, EPEAT Gold, TÜV Flicker-free, TÜV Low Blue Light (Hardware Solution), VESA MediaSync Display, Calman Verified, Mac compliance

* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice

ASUS