


41092089

SCHUKO socket outlet with LED orientation light enhanced contact protection, Screw-in lift terminals, Serie 1930/R.classic, polar white glossy

Technical features

Architecture

Design	according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Power

Power consumption	0.25 W/0.35 VA

Cover, door

- Central cover plate

Detection

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour of labelling	105,105,105
Colour	white
Colour	polarwhite
Material	thermoplastic
Material for printing	ASA polar white
Surface appearance	glossy

Dimensions

Insertion depth	32 mm

Lighting control

Light intensity (white)	0,2 cd
Switch-off brightness	≈ 4 lx
Switch-on brightness	≈ 2 lx

LED control

- white LED light
- long service life of the LED

Installation, mounting

- with spreader claws

Connection

Conductor cross-section (rigid)	max. 2,5 mm²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with screw-in lift terminals

Cable

- through-wiring possible, therefore also ideal for retrofitting

Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

Equipment

Type of configuration	Laserdruck

- additional benefit by combination of a socket outlet with an orientation light

Use

- enhanced contact protection
- Screw-in lift terminals

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	05
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Main design line	Serie 1930/R.classic

Instructions

- Caution!
  Items with special flush-mounted insert.
  Centre plates with LED orientation lights are not compatible with the standard socket outlets.
- Note:
  When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!