

SUB12

Product sheet

MADE IN
FRANCE

Sub12 is a highly articulate subwoofer offering a level of definition, dynamics and sub-bass that is unrivalled in its price bracket. Thanks to its high excursion woofer and 1000W peak amplification, the Sub12's transcription is more powerful and truer than ever.



Key points

- Composite sandwich 'W'-cone: sound neutrality, no distortion
- Large laminar port: no port noises or distortion
- Automatic disengageable stand-by mode
- Amplification: 600W RMS, 1000W peak
- Carry handle

Type	Subwoofer	
Frequency response (@ -3dB)	30Hz - 400Hz	Internal signal processing and functions - Subwoofer section
Low cut-off frequency (@ -6dB)	28Hz	
Maximum SPL (Average CEA2010B 30-200 Hz free field @ 1m)	124.5dB	
Inputs	Balanced XLR LFE 10k Ω , Left & Right 10k Ω	
Outputs	Balanced XLR LFE (in parallel), Left & Right 50 Ω	Outputs (to satellites) - Type/Impedance - Connector
Bass amplifier stage	600W RMS	Right, left Electronically balanced / 50 Ω 3-point male XLR
Nominal power supply	-100-120 VAC/220-240 VAC 50/60Hz	Bass
User controls	Sensitivity, Stand-by, Polarity, Phase, LPF, Volume, HPF	1 x 13" (33cm) x 'W' cone
Fuses	-100-120V, T10AL/250V -220-240V, T5AL/250V	Shielding
		No
		Construction
		Dark red natural veneering side panels, black body
		Dimensions (HxWxD)
		23 ^{5/8} x19 ^{1/8} x22 ^{3/8} " (60x48.7x56.8cm)
		Weight
		127.8lbs (58kg)
		Temperature range
		During use: 5-35°C In storage: 0-50°C