

## 2U Vented Sliding Rack Shelf w/ Cable Management Arm & Adjustable Mounting Depth - 125lbs / 56.7kg

Product ID: UNISLDSHF19M



The UNISLDSHF19M Adjustable Sliding Rack Shelf lets you add a vented, sliding shelf with cable management into virtually any 4-post server rack or cabinet. This TAA compliant product adheres to the requirements of the US Federal Trade Agreements Act (TAA), allowing government GSA Schedule purchases.

The adjustable mounting depth design allows the shelf to be installed easily into server cabinets with mounting depths from 27.7in (702.2mm) to 31.6in (802.2mm). The sliding rails also offer a locking mechanism to stop the shelf from sliding out too far, or sliding back into the rack before maintenance is complete.

Offering a weight capacity of up to 125 lbs (56.7 kg), this sliding rack shelf features a ventilated, cold-rolled steel construction for increased airflow and durability in your server room or wiring closet installations.

For ease in routing cables neatly through your rack, we've included a reversible cable management arm that can be attached to the back of the shelf, plus an adjustable bezel to keep your equipment where you want it on the shelf.

Backed by a StarTech.com 2-year warranty.

### Certifications, Reports and Compatibility



### Applications

- Supply additional storage space for hardware or non-rackmount equipment and peripherals
- Install into virtually any standard 4-post rack or cabinet

### Features

- Supports up to 125lbs (56.7kg)
- Adjustable mounting depth from 27.7in (702.2mm) to 31.6in (802.2mm)
- TAA compliant for GSA Schedule purchases
- Includes a reversible cable management arm
- Vented shelf for increased airflow
- Sliding rails with locks to prevent the shelf from sliding out too far
- Sturdy, 2mm cold-rolled steel construction

|                                 |                           |                                                |
|---------------------------------|---------------------------|------------------------------------------------|
| <b>Hardware</b>                 | Warranty                  | 2 Years                                        |
|                                 | Industry Standards        | EIA RS310-D                                    |
|                                 | Mounting Options          | Front Mount (Front and Rear)                   |
|                                 | U Height                  | 2U                                             |
| <b>Performance</b>              | Weight Capacity           | 125.3 lb [56.7 kg]                             |
| <b>Physical Characteristics</b> | Color                     | Black                                          |
|                                 | Enclosure Thickness       | 0.1 in [2 mm]                                  |
|                                 | Enclosure Type            | Steel                                          |
|                                 | External Depth            | 24 in [609.6 mm]                               |
|                                 | External Height           | 3.4 in [85.2 mm]                               |
|                                 | External Width            | 19 in [483 mm]                                 |
|                                 | Maximum Mounting Depth    | 31.6 in [802.2 mm]                             |
|                                 | Minimum Mounting Depth    | 27.6 in [702.2 mm]                             |
| <b>Packaging Information</b>    | Shipping (Package) Weight | 21.8 lb [9.9 kg]                               |
| <b>What's in the Box</b>        | Included in Package       | 1 - Shelf Assembly                             |
|                                 |                           | 2 - Ear Hook and Slide Assembly (Left / Right) |
|                                 |                           | 2 - Ear Hook Bracket (Left / Right)            |
|                                 |                           | 1 - Cable Management Assembly                  |
|                                 |                           | 1 - Instruction Manual                         |

Product appearance and specifications are subject to change without notice.