ViewSonic

LCD DISPLAY

VA2406-h-2

Key **Features**

- SuperClear® VA panel
- Eye-care technology for comfortable viewing
- Eco-mode for low energy consumption
- ViewMode color rendering options
- HDMI and VGA inputs for connectivity



Product **Description**

The ViewSonic VA2406-h-2 is a 24” Full HD monitor with HDMI and VGA input for business or home usage. Delivering a stunning image quality with low power consumption, this monitor provides six ViewMode presets that deliver optimized screen performance based on your needs. The eye care technology that comes standard with all VA monitors helps to eliminate eyestrain from extended viewing periods. A VESA-compatible mount makes this monitor is easy to setup on the wall or with a wide range of industry-standard mounts.



1. Menu Control Panel
2. VESA Compatible(Wall Mount 100 x 100mm)
3. HDMI
4. VGA
5. Earphone
6. DC in

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	VA Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	5,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ), sRGB: 104% size (Typ)
Pixel Size:	0.275 mm (H) x 0.275 mm (V)
Surface Treatment:	Anti-Glare (Semi-Glossy), Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
Power in:	External power adapter

POWER

Eco Mode (Conserve):	18W
Eco Mode (optimized):	22W
Consumption (typical):	25W
Consumption (max):	27W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.3W
Power Supply:	External

ADDITIONAL HARDWARE

Kensington Lock Slot:	1

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm

INPUT SIGNAL

Frequency Horizontal:	24 ~ 86KHz
Frequency Vertical:	50 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-3º / 20º

WEIGHT (IMPERIAL)

Net (lbs):	7.5
Net Without Stand (lbs):	6.6
Gross (lbs):	10.6

WEIGHT (METRIC)

Net (kg):	3.4
Net Without Stand (kg):	3
Gross (kg):	4.8

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	24.5 x 16.5 x 5.7
Physical (in.):	21.2 x 16.6 x 7.4
Physical Without Stand (in.):	21.2 x 12.7 x 2

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	622 x 420 x 144
Physical (mm):	540 x 423 x 189
Physical Without Stand (mm):	540 x 323 x 51

GENERAL

Regulations:	CE, CE EMC, LVD, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA, BSMI, RCM, GEMS, BIS
PACKAGE CONTENTS:	VA2406-H-2 x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market

Copyright © ViewSonic Corporation 2000-2021. All rights reserved.