

Product datasheet

Specifications



modular single phase power meter iEM2010 - 230V - 40A with pulse

Local distributor code:
399395170

A9MEM2010

EAN Code: 3606480217418

Main

Range	Acti9
family	Acti9 iEM2000
Device short name	iEM2010
Product or component type	Energy meter

Complementary

poles description	1P + N
Type of measurement	Active power
Device application	Sub billing
Accuracy class	Class 1 active energy conforming to IEC 62053-21 Class B active energy conforming to EN 50470-3
Input type	Direct input
Maximum current [Imax]	40 A
[Ib] basic current	5 A
Rated current	40 A
Rated voltage	230 V +/- 20 %
Network frequency	50 Hz 60 Hz
Frequency measurement range	48...62 Hz
Technology type	Electronic
Display type	Electromechanical
Sampling rate	32 samples/cycle
Measurement current	0.25...40 A
Display digits	7
Maximum value measured	999999.9 kWh
Communication port protocol	-
Communication port support	-
Local signalling	Green indicator light: power ON Yellow indicator light: metering and activity 3200 p/kWh
Digital inputs	0
Digital outputs	1 pulse energy monitoring:
Output voltage	5...35 V DC@20 mA
Impulse duration	120 ms

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum power consumption in VA	10 VA at 240 V AC
mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Power circuit: tunnel type terminals (bottom) 1 10 mm² cable(s) Remote transfer: tunnel type terminals (top) 1 4 mm² cable(s)
Tightening torque	Power circuit: 1.2 N.m Remote transfer: 0.8 N.m
Standards	IEC 62053-21 IEC 61557-12 EN 50470-3
Product certifications	CE EAC EAC (metrology) MID-B MID-D

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 casing:
Ambient air temperature for operation	-10...55 °C -20...55 °C
ambient air temperature for storage	-40...70 °C
Operating altitude	< 2000 m
Relative humidity	0...95 % at 55 °C
Colour	White
9 mm pitches	2
Width	18 mm
Height	96.5 mm
Depth	69 mm
Net weight	0.073 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.3 cm
Package 1 Width	7.3 cm
Package 1 Length	10.0 cm
Package 1 Weight	123.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	38
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	5.015 kg

Contractual warranty

Warranty

18 months

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓

Mercury Free

✓

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information