

Specifications

LCD Panel	Drive System	TFT Color LCD
	Size	34"
	Pixel Pitch	0.23175 (H) – 0.23175 (V)
	Brightness	400nits (Max.)
	Contrast	3000:1
	Visible Angle	178° (Horizontal) 178° (Vertical)
	Response Time	1ms (MPRT) , OD 4ms (G to G)
	Panel Type	VA
	Horizontal Frequency	71.52- 214.56 KHz
	Vertical Frequency	48- 144 Hz
Display Color		16.7 million colors
Maximum Resolution		DP 1.4: 3440 x 1440 144Hz HDMI 2.0: 3440 x 1440 100Hz
Power consumption	AC Input Power	54W Typical, 80W Max
	Standby Power (Maximum)	Standby ≤ 0.5W
Input Connector		(DP) (DP models only) HDMI (HDMI models only)
Input Video Signal		DP Signal (DP input models only) HDMI Signal (HDMI input models only)
Speakers		3W x 2
Audio effect		Audio Output (Audio output models only)
Adapter		100-240V AC, 50/60Hz 2A
Environmental Conditions		Operating Temperature: 0°C~40°C Storage Temperature: -20°C~60°C Operating Humidity: 10~85%RH
Machine Dimensions		808.65*520.82*263.9mm
Weight (Net Weight)		6.2 KG / Unit (Net Weight)
Machine Specifications		Tilt: -5° to +15° Rotation: Can be rotated to either the left or right by 45 degrees Height Adjustment: Lifting base; stroke 0-100mm Removable Stand: Yes
Regulatory Compliance		
		
		
HDMI, HDMI high definition multimedia interface and the HDMI logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the U.S. and other countries.		

If you have any usage problems, please visit: <https://www.coolermaster.com/warranty>