

Art No. PL0008

500Mbps Powerline Ethernet Mini Adapter, Duo Pack

ogiLink

HD entertainment and fast home network in one: with speeds of 500 Mbps, the Powerline PL0008 is powerful enough to transmit even 3D movies to every room of your home. Without routing cables or WLAN picture stutter - simply over the electrical wiring. Connect computers, laptops, game consoles as well as Internet TVs and hard drive recorders to each other and to the Internet. The first powerline adapter of the latest generation is fully compatible with all 200 AV adapters, is extremely energy saving and, thanks to its flat, inconspicuous design, can be positioned anywhere.

Features:

LogiLink

• 🔓

- IEEE1901 and HomePlug AV Compliant
- Co-existence with HomePlug 1.01
- High transfer rate of up to 500 Mbps
- For all types of bandwidth-intensive transmission
- High Definition (HD) and Standard Definition (SD) video distribution
- Internet Protocol Television (IPTV) distribution
- Home networking backbone for Wi-Fi, and Wireless USB
- High speed broadband sharing
- Audio and video streaming and internet downloading
- PC files and applications sharing
- Printer and peripheral sharing
- Network and interactive online gaming
- Security cameras
- Supports low power "Standby" mode for 2013 EuP Standard
- Full compatibility with all 200 and 500 HomePlug AV adapters





RoHS



Art No. PL0008

500Mbps Powerline Ethernet Mini Adapter, Duo Pack

LogiLink

Specification:

LogiLink.

• U • E • A

PLC Signal	Frequency band 2 – 68 MHz (With Mask)
	Modulation OFDM (Supports OFDM 4096/1024/256/64/16/8-
	QAM, QPSK, BPSK and ROBO Modulation Schemes)
	FEC (Forward Error Correction) Coding
	Frequency Notching support
	PHY Rate: 500Mbps
	TCP: Up to 97 Mbps effective throughput
	UDP: Up to 97 Mbps effective throughput
Access Methods	TDMA and priority-based CSMA/CA channel access schemes
	maximize efficiency and throughput
	Integrated Quality of Service (QoS) Enhancements
	Hardware Packet Classifiers for ToS, CoS and IP Port Number
	Supports IGMP managed multicast sessions
	Auto-MDI/MDI-X negotiation and sensing for 10/100 Ethernet
QoS	4 Levels priority based contention access & multi segment bursting
	8 Levels VLAN priority field
Nodes	Up to 15 slaves with 1 master, 16 total devices
	It supports max. 8 nodes at home
IGMP	Supports IGMP managed multicast sessions
	Hardware Packet Classifiers for ToS, CoS and IP Port Number
Security Encryption	128-bit AES Link Encryption with key management
Distance	AC Wire; 200 meter
Standards	IEEE 802.3, IEEE 802.3u, HomePlug AV 1.01, IEEE 802.1p, IEEE
	1901
Push button	Network Setup button for Network Security Management and
	Factory default reset button
Port	One 10/100 Ethernet RJ45 port



RoHS compliant

* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.



500Mbps Powerline Ethernet Mini Adapter, Duo Pack

Art No. PL0008

ogiLink

Specification:


Electrical	Power Supply: 100-240 VAC 50/60Hz
	Power Consumption: 4W Max. (Standby Mode: 0.45W)
Operating System	Window 98SE/Me/NT2000/XP/Vista/Win 7, MAC and Linux
Environmental	Operating Temperature: 0~45°C
Temperature	Preserve Temperature: 0~70°C
Relative Humidity	Operating: 10~90% non-Condensing
	Preserve: 10~95% non-Condensing
Physical	Dimensions (L x W x H): 67x50x32 mm (With Plug)
	Weight: 97g (Wall Mount Type)
LED	Power (Green, Blinking at standby mode)
	Link (Green/Orange/Red throughput indicator)
	Ethernet (Green)

Package Content:

- 2 x Powerline Ethernet Adapters
- 2 x CAT5e Cable, 1.2M
- 1 x Quick Installation Guide
- 1 x CD (Software & Manual)

Packaging Information:

- Packing Dimension: 190 x 152 x 74.6mm
- Packing Weight: 320g
- Carton Dimension: 378x350x333 mm
- Carton Q'ty: 20pcs
- Carton Weight: 6.4kgs



RoHS compliant





* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.

Made in China