

DIGITUS[®] Modular Patch Panel for Keystone Modules



✓ Modular

✓ 24-port

✓ For 483 mm (19") mounting

✓ Available in colors black and grey

Abstract

DIGITUS[®] Modular Patch Panel for Keystone Modules, shielded, 24-port, 1U, 19" rack mount

Features

- Compatible with DIGITUS[®] CAT 5e, CAT 6, CAT 6_A Keystone Modules
- Inclusive earthing lead
- Compatible with shielded and unshielded DIGITUS[®] Keystone Modules
- Available in colors grey (RAL 7035) and black (RAL 9005)
- The modular version is perfect for standard and pre-terminated installations
- Delivery content with rear management tray
- Operating temperature: -20 °C up to +75 °C
- Material of housing: SPCC, 1.5 mm cold rolled C-steel, acc. to JIS G3141-1996
- Suitable for 483 mm (19") Rack mount
- Hight Unit: 1U

Product Overview

The modular patch panel from DIGITUS[®] is specially designed for 19" rack installation and for mounting of DIGITUS[®] Keystone Modules. The modular patch panel is available in two different colors: Grey (RAL 7035) and black (RAL 9005). The housing material is SPCC, 1.5 mm cold rolled C-steel in compliance with JIS G3141-1996. The rear management tray with special designed cable tie positions, is delivered as snap-in tool for simple installation. An earthing kit is also supplied with the modular patch panel.

Product Number Information

DN-91410	DIGITUS [®] Modular Patch Panel, shielded, 24-Port, blank, 1U, rack mount, color grey (RAL 7035)
DN-91411	DIGITUS [®] Modular Patch Panel, shielded, 24-Port, blank, 1U, rack mount, color black (RAL 9005)


Product Number Information - Keystone Modules - Category 6 shielded

DN-93612	DIGITUS® CAT 6 Keystone Module, shielded, class E _A , RJ45 to LSA, tool free installation
DN-93614	DIGITUS® CAT 6 Keystone Module, shielded, class E _A , RJ45 to LSA, tool free installation
DN-93615	DIGITUS® CAT6 _A Keystone Module, shielded, Re-embedded, 500 MHz acc. to ISO/IEC 11801:2002, AM2:2009/09, tool free installation
DN-93617	DIGITUS® CAT 6 _A Keystone Module, shielded, 500 MHz acc. to ISO/IEC 60603-7-51, 11801, AMD2:2010-04, tool free installation

Product Number Information - Keystone Modules - Category 6 unshielded

DN-93601	DIGITUS® CAT 6 Keystone Module, unshielded, RJ45 to LSA, color black
DN-93602	DIGITUS® CAT 6 _A Keystone Module, unshielded, class E _A , RJ45 to LSA, tool free installation
DN-93603	DIGITUS® CAT 6 Keystone Module, unshielded, RJ45 to LSA, tool free installation, incl. cable tie
DN-93604	DIGITUS® CAT 6 _A Keystone Module, unshielded, 500 MHz acc. to ISO/IEC 11801:2002, AM2:2009/09, tool free installation

Technical Drawings



Specification:

1. Support Bar: SPCC, 1.5MM Thickness with Grey or Black Color Painted.
2. Front Panel: SPCC, 1.5MM Thickness with Grey or Black Color Painted.
3. Rear Panel: SPCC, 1.5MM Thickness with 5-8um Nickel plated.
4. Ground Wire: 18 AWG Wire, with Green/Yellow striped color, Length 40cm.

