



USB-C to HDMI 3-in-1 Docking Converter with Power Delivery

USB 3.2 Type-C Male to HDMI (4K@30Hz), USB-A (5 Gbps) and USB-C PD (100 W) Females, Multiport Converter with Pass-through Charging Port, Black

Part No.: [130622](#)

EAN-13: 0766623130622 | UPC: 766623130622

USB-C to HDMI Adapter to connect a laptop, MacBook®, smartphone or tablet to an HDMI display - plus USB-A peripheral and Power Delivery charging port

The Manhattan USB-C 3-in-1 HDMI Docking Converter with Power Delivery establishes a fast, simple and convenient link between newer USB type-C equipped media sources (laptops, PCs, MacBooks, Chromebooks, computers, tablets, etc.) and existing HDMI displays (monitors, TVs, and projectors) for 4K at 30 Hz images in either mirror- or extended-display mode. Create a mini-workstation by adding any USB 3.2 Gen 1 (formerly USB 3.0) peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB-A port. This multiport Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your USB-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Up to 100 W charging power with USB-C Power Delivery (PD)

The included USB-C PD port lets you charge your notebook with power up to 100 W while simultaneously charging your other mobile devices, such as smartphones or tablets, through the USB-A port. The Power Delivery function also provides faster charging than standard chargers since it determines the power needs of compatible devices and supplies it at the quickest and safest rate.

Take your phone to the big screen

If you have a smartphone or tablet that supports video output over USB-C DP Alt Mode, you can enjoy your apps and media even more. Watch a video on your monitor or flip through the slides of your presentation on a projector - all from your phone.

A multiport adapter that's made to go where you go

The very compact housing makes this USB-C to HDMI Adapter the perfect travel companion. With a footprint of only 52 x 59 x 12 mm (2.05 x 2.32 x 0.47 in.), it's small enough to fit in an outer notebook bag pocket, so you can create a mini-workstation for your laptop where ever you're going.

Features:

- Easily connects a USB-C device to an HDMI display and USB-A peripheral while also charging both USB devices
- Resolutions up to Ultra-High-Definition (UHD) 4K@30Hz (3840 × 2160)
- One USB 3.2 Gen 1 Type-A port (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps and charging up to 7.5 W (5 V / 1.5 A)
- USB-A port to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- Supports USB Power Delivery (PD) function up to 100 W; requires an external PD charger - available from Manhattan
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple[®] MacBook[®], Chromebook[™], Pixel[™] and more
- Built-in, sturdy 10 cm (4 in.) cable
- Fully HDCP 1.4 compliant, backward compatible
- Lets your smartphone work like a desktop PC while also charging it (desktop setup requires devices with Android 9 or above that offer video output over USB-C)
- Plug-and-play installation; Windows[®], macOS[®], Linux[®], Chrome OS[™], iPadOS[®] and Android[™] compatible
- Three-year warranty

Specifications:

Standards and Certifications

- DP 1.2 Alt Mode over USB-C
- USB 3.2 Gen 1
- HDMI 1.4
- HDCP 1.4

- CE
- FCC
- RoHS
- REACH
- UKCA

General

- USB-A port data transfer speed: 5 Gbps
- Bus powered operation (except charging functions)
- USB-C PD charging port: 100.0 W (20.0 V at 5.0 A) max.
- USB-A charging: 7.5 W (5.0 V at 1.5 A) max.

Connections

- One USB-C 24-pin, male
- One USB-C 24-pin, female
- One USB-A 4-pin, female
- One HDMI 19-pin, female

Physical

- Dimensions (L x W x H): 52 x 59 x 12 mm (2.05 x 2.32 x 0.47 in.)
- Net weight: 29 g (1.02 oz.)
- Gross weight: 65 g (2.3 oz.)
- Cable length: 10 cm (4 in.)
- Cable diameter: 34 AWG
- Plastic housing

Operating Environment

- Operation temperature: 0 - 45°C (32 - 113°F)
- Storage temperature: -10 - 70°C (14 - 158°F)
- Humidity (noncondensing): 5 - 90% RH

System Requirements

- Windows 7/8.1/10/11, Linux, Chrome OS, macOS, iPadOS or Android

Package Contents

- USB-C to HDMI 3-in-1 Docking Converter with Power Delivery
- Instructions



