



30483515

**Double change-over switch insert with rocker 2gang surface-mounted/flush-mounted, isolated input terminals Berker W.1**

Technical features

**Architecture**

Type of control unit	double rocker
Technical version	isolated input terminals

**Controls and indicators**

- No

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Switching current	10 AX
-------------------	-------

**Materials**

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey
Colour	dark grey
Material	thermoplastic
Surface appearance	mat

**Dimensions**

Depth	42 mm
Height	70 mm
Width	70 mm

**Installation, mounting**

- for screw fastening

**Connection**

Type of connection	Quickconnect
- with plug-in terminals	

**Equipment**

- without lighting (cannot be illuminated)

**Safety**

Protection index IP	IP55
---------------------	------

**Use conditions**

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

- 
- Pins of quick-release lock made of ZAMAK
  - Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.
-