

TS-883XU-E2124-8G	
CPU	Intel® Xeon® E-2124 quad-core 3.3 GHz processor (burst up to 4.3 GHz)
CPU Architecture	64-bit x86
Floating Point Unit	Yes
Encryption Engine	Yes (AES-NI)
System Memory	8 GB UDIMM DDR4 ECC (2 x 4GB)
Maximum Memory	64 GB (4 x 16 GB)
Memory Slot	4 x DDR4 long DIMM
Flash Memory	4GB (Dual boot OS protection)
Drive Bay	8 x 3.5-inch
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Hot-swappable	Yes
SSD Cache Acceleration Support	Yes
Gigabit Ethernet Port (RJ45)	4
10 Gigabit Ethernet Port	2 x 10GbE SFP+ SmartNIC port
Jumbo Frame	Yes
PCIe Slot	4 Slot 1: PCIe Gen2 x4 (PCH) Slot 2: PCIe Gen3 x8 (CPU) Slot 3: PCIe Gen3 x4 (CPU) Slot 4: PCIe Gen3 x4 (CPU) Slot 4 is preinstalled with a 10GbE network adapter
USB 3.1 Gen 2 (10Gbps) Port	2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 4 x Type-A USB 3.1 Gen2 5V/1A 10Gbps
Form Factor	2U Rackmount
LED Indicators	HDD 1-8, Status, LAN, storage expansion port status
Buttons	Power, Reset
Dimensions (HxWxD)	88.3 × 482 × 562 mm
Weight (Net)	10.39 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)

Power Supply Unit	350W, 100-240V
Power Consumption: Operating Mode, Typical	72.16 W With drives fully populated
Fan	System: 2 x 6.0cm fan (12V DC)
Sound Level	40.3 db(A)
System Warning	Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.