



Installation der SQE1-Serie mit 4K-Auflösung auch im Hochformat, 24/7-Dauerbetrieb, starke Helligkeit mit 500 cd/m², umfangreiche Anschlussmöglichkeiten. Das Produkt eignet sich für den Einsatz an öffentlichen Plätzen und in gewerblichen Einrichtungen.

TH-75SQE1

Viermal höhere Auflösung als bei Full HD für eine detailreiche Anzeige bewegter Bilder in 4K/60p. Die Displays eignen sich für zahlreiche Anwendungen, und ihr Design fügt sich nahtlos in die Umgebung ein. Installation im Hochformat möglich. 24/7-Dauerbetrieb. Ideal für die

Key Features

4K mit 75" und 500 cd/m² mit schlankem und elegantem Design, geeignet für Dauerbetrieb


4K-USB-Media-Player: Externe Geräte werden überflüssig und Updates über LAN ermöglicht

Steckplatz nach Intel® SDM-Spezifikation (Smart Display Module). Ausgestattet mit 4 HDMI-Anschlüssen, USB Typ A und C, DP (Ein-/Ausgang), Unterstützung von HDMI CEC

WLAN-Funktion und HTML5-Browser integriert

Flexible und einfache Installation in Hoch- oder Querformat





TH-75Sqe1

<https://eu.connect.panasonic.com/de/products/professional-displays/th-75sqe1>

Screen size (diagonal) (inch)	75-inch class (1892.7 mm)
Panel Type	D-LED
Aspect Ratio	16:9
Effective display area (W x H) (mm)	1649.6 x 927.9 mm
Effective display area (W x H) (inch)	64.94" x 36.53"
Auflösung	3840 x 2160
Brightness (typ.)	500 cd/m2
Contrast Ratio	1200:1
Response Time	8.0 ms (G to G)
Viewing angle [(T/B)/(L/R)]	178° / 178° (CR>10)
Panel Surface Treatment	Anti-Glare Low Reflection (Haze 3 %)
Terminals HDMI In	HDMI TYPE-A Connector x 4 (HDCP 2.2 supported)
Terminals DisplayPort IN	DisplayPort x 1
Terminals DisplayPort OUT	DisplayPort x 1
Terminals PC In	Mini D-sub 15-pin x 1 (Female)
Terminals Serial	D-sub 9-pin x 1 (Female), RS232C Compatible
Terminals IR In	Stereo Mini Jack (M3) x 1
Terminals Audio In	Pin Jack x 2 (L/R)
Terminals Audio Out	Stereo Mini Jack(M3) x1, SPDIF x 1
Terminal LAN	RJ45 x 1
Terminals Slot	x1 (Intel® SDM Specification Capability)
Terminals USB	USB Connector (TYPE-A) x 2, (Type-C) x 1, Internal (Type-A) x 1
Wi-Fi	Built-in, IEEE 802.11. a/b/g/n/ Dual Wi-Fi CERTIFIED
Built-in Speaker	24 W [12 W + 12 W]
Power Requirements	110~127 V AC, 50/60 Hz, 220~240 V AC, 50/60 Hz
Power Consumption	334 W
Power Off Condition	0 W
Stand-by Condition	Approx. 0.5 W
Dimensions (W x H x D) (mm)	1684 x 968 x 100 mm *Excluding remote IR sensor
Dimensions (W x H x D) (inch)	66.28" x 38.09" x 3.92" *Excluding remote IR sensor
Weight (kg)	Approx. 37.4 kg
Weight (lbs.)	82.5 lbs
Bezel width (mm)	15.7 mm (T/R/L), 21.5 mm (B)
Bezel width (inch)	0.62" (T/R/L), 0.85" (B)
Wall-hanging pitch (mm)	VESA Compliant 600 x 400 mm
Wall-hanging pitch (inch)	VESA Compliant 23.7" x 15.8"
Orientation*1	Landscape/Portrait
Tilting angle*2	0-20 degrees forward with landscape/portrait setting
Operating time*3	24 h/day
Operating Environment	Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)
Note	*1: When installing the display vertically, be sure that the power indicator comes to the right side. *2: Please contact your sales representative with regard to the tilt angle before installation. *3: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.