

DELTA Shaving socket, titanium white cover plate 80x 80 mm 20VA, 230 V 50/60 Hz



Model	
Cover version	others
Design of the special power supply unit	without special current supply
Design of the socket / according to VDE 0620 for severe conditions	No
Design of the phase tap	No
General technical data	
Marking / of socket outlet (mounting type)	others fixing with screw
Surface processing	others
Material	thermoplastic
Protection class	
Protection class IP	IP44
Main circuit	
Operating voltage / Rated value	230 V
Operating current / Rated value	20 A
Appearance	
Color	white

Product details

Product component	
• Ejection equipment	No
• Labeling field	No
• Increased touch protection	No
• Fault current protection	No
• miniature fuse	No
• Integrated / functional lighting	No
• Integrated / Light source	No
• Integrated / orientation lighting	No
• Hinged lid	No
Product feature	
• lockable	No
• halogen-free	Yes
• transparent	No

Product function

Product function	
• Socket selectable	No
• Overvoltage protection	No

Number

Number of units	1
Number of sockets / switchable	0

Connections

Arrangement of contacts / diagonal	No
Type of electrical connection	others

Mechanical Design

(height)	85 mm
Width	85 mm
Depth	62 mm
(mounting type)	flush mounted
Material / of the enclosure	plastic

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5UA6701>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5UA6701>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5UA6701

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

