



IPower Switch Classic 16

No.: 32658

Control the power of up to 16 devices

Description

- Remote management switch for up to 16 computers or other devices
- Control via simple to use browser interface or software
- Built-in web server, supports real time monitoring for the current consumption of the power strip
- TAA compliant
- 2 year warranty

The Lindy IPower Switch Classic 16 is a power management solution which connects to an existing network infrastructure to provide convenient remote control power management. System administrators can control the power of multiple servers, workstations, hubs, router etc. allowing reboot and power-on and off functions, via a simple to use browser interface or via software.

Each outlet has its own status indication LED and the display shows the current IP address of the unit directly. Power consumption charts for daily, monthly or a user-defined period are available.

Please note that SSL is not supported.

Please note: This product does not come with a mains power cable. These are available from Lindy using part number 30459 or 30344.

This unit has an IEC 320 C19 mains power input connector capable of operating from a 16A circuit. The suggested power cable is a standard Mains plug fused at 13A. If you intend to connect the unit to a 16A circuit then please ensure you use an appropriate Commando style plug to IEC 320 C19 power cable rated at 16A.

Technical details

Specifications

- Input Voltage: 110-240V
- Switched Power [per port]: max. 2400W [240V 10A]
- Switched Power [total]: max. 3120W [240V 13A or 240V 16A using optional "Commando" to IEC C19 Power Cable]
- Nominal Input Frequency: 47-63 Hz Full Range
- Current Range: 0A~20A [True RMS]
- Current Amperage: 0A~20A: +/- 2% [+/- 0.1A]
- Current Meters: 3 digits
- LED Indicators: 1x yellow LED, 1x red LED

Connectors

- Input: IEC C20

Output: 14x IEC C13, 2x IEC C19

Network Connection : RJ45 10Mbps Ethernet Port

Physical Properties

Dimensions [approx.] WxDxH: 1255x55x45mm (49.41x2.17x1.77in)

Housing Material: Metal

Net Weight: 3kg (6.61lb)

Operating Temperature: -5_45°C (23°F_113°F)

Storage Temperature: -25_65°C (-13°F_149°F)

Humidity: 0-95% (non-condensing)

Colour: Black

Miscellaneous

Packaging Type: Carton

Packaging Dimensions: 1355x210x106mm (53.35x8.27x4.17in)

Gross Weight: 4.2kg (9.26lb)

Warranty (Years): 2

Certification: CE, UKCA, FCC, RoHS, REACH, EMC, LVD, TAA

Package Contents

1 Power Switch Classic 16

Rack mount brackets and screws

Lindy Quick Installation Guide

Purchasing Information

No.: 32658

EAN: 4002888326582