

Wiha Bit holder with handle.

Bit holder 1/4".



384 Bit holder with handle, magnetic, 1/4".

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
 Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
 Bit holder: Stainless steel with strong magnet.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.

Order-No.	Ø	↔	↔	↕	↔
01475	1/4	125	225	36	10
01476	1/4	300	400	36	5



386 Bit holder with handle, flexible shaft, 1/4".

Blade: Plastic coated flexible metal.
 Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
 Bit holder: With retaining ring.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
 Application: For offset screws.

Order-No.	Ø	↔	↔	↕	↔
01479	1/4	150	268	36	10



387 Bit holder with handle, quick release holder, 1/4".

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
 Bit holder: ClicFix quick release holder, magnetic.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
 Application: Compact, handy style for working in confined spaces.
 For applications where the bit must be held tight.

Order-No.	Ø	↔	↔	↕	↔
25874	1/4	35	146	30	10



281-02 Bit holder with handle, magnetic, 1/4".

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
 Bit holder: Stainless steel with strong magnet.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.
 Application: Compact screwdriver together with bits, 1/4".
 Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.	Ø	↔	↕	↔
32160	1/4	125	36	10

Bit holder 1/4".



281 01 Bit holder with handle, magnetic, 1/4".

Handle: Ergonomic Wiha Stubby SoftFinish® handle, multi-component with roll-off protection.
 Bit holder: Stainless steel with strong magnet.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
 Application: For working in confined spaces.
 Extra: Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.	Ø	↔	↕	↔
29463	1/4	57	34	10



281-01ESD ESD bit holder with handle, retaining ring, 1/4". Dissipative handle, ESD-safe.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
 Surface resistance $10^6 - 10^9$ ohms.
 Universal use for all bits.
 Standards: Handle: IEC 61340-5-1.
 Output: For bits according to DIN 3126, ISO1173 style C 6.3.
 Bit holder: Stainless steel with retaining ring.
 Application: For working on electrostatically sensitive components, especially in tight places.

Order-No.	Ø	↔	↕	↔
32484	1/4	57	34	10



387ESD ESD bit holder with handle, quick release holder, 1/4". Dissipative handle, ESD-safe.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
 Surface resistance $10^6 - 10^9$ ohms.
 Standards: Handle: IEC 61340-5-1.
 Output: For bits according to DIN 3126, ISO1173 style C 6.3, E 6.3 and double bits.
 Input: DIN 3126, ISO 1173, style E 6.3.
 Bit holder: Stainless steel with retaining ring.
 Application: For working on electrostatically sensitive components.
 With integrated CentroFix bit holder, suitable for all bits and bit drills with the style C 6.3, E 6.3 or double bits.
 Extra: True single-handed operation, extremely high retention force of bits (up to 20 kg) and virtually no play between bit and holder thanks to special closing and holding mechanism.

Order-No.	Ø	↔	↔	↕	↔
32161	1/4	38	148	30	10