

## Nature Wild Cam 8MP TX-125

Security camera battery operated for indoor and outdoor use



Videoaufnahmen FullHD 1080p / Video Recording FullHD 1080p



Fotoaufnahmen 21MP / Photo Shooting 21MP



Weitwinkel 100° / Wide Angle 100°



Batteriebetrieb / Operating with Batteries



0,5 Sekunden Auslösezeit / Triggering Time 0.5 seconds



2,4" TFT Farb-Display / 2.4" TFT Colour Display



Integriertes Mikrofon & Lautsprecher / Built-in Microphone & Speaker



PIR-Sensor / PIR Sensor



IR-Reichweite bis zu 18m / IR Range up to 18m



IR-LEDs für Nachtaufnahmen / IR LEDs for night recordings



MicroSD Karte bis zu 32GB / MicroSD Card up to 32GB



Schutzklasse IP56 / Protection Class IP56

- Ideal for recording and observing the wildlife and for monitoring houses
- FullHD video resolution 1080p
- 2.4" TFT LCD display (720x320)
- Select functions: video, photo, video & photo
- PIR sensor (~18m) & IR range (~18m) for night recordings
- Triggering time 0.5 seconds
- Built-in microphone & speaker
- MicroSD card\*\* up to 32GB (\*\*not included)
- Camera protection class IP56 (dust proof & heavy splash water proof)



### Technical Specifications:

- Image sensor 1/3.2" CMOS 8MP
- Video resolution: 1920x1080/25fps (interpolated), 1280x720/30fps, 720x480/30fps, 640x480/30fps, 320x240/30fps
- Photo resolution: 21MP (5616x3744 interpolated), 16MP (4608x3456 interpolated), 12MP (4000x3000 interpolated), 8MP 3264x2448), 5MP (2592x1944), 3MP (2048x1536)
- Video length 3 sec.–10 min. programmable
- File format JPEG / AVI
- Lens: f=3.3mm, F/NO2.0, FOV=100°, Auto IR filter
- Trigger interval 5 sec.–60 min. programmable
- Time lapse function 3 sec.–24 hours programmable
- Power supply: 8x AA batteries\* (\*included); external 6V/at least 1.5A
- Standby time ~12 months
- Working temperature -20°C ~ +60°C
- Weight / Dimensions: 335g (without batteries) / (L) 9.6 x (W) 8.1 x (H) 13.6cm

### Package Contents:

Nature Wild Cam 8MP TX-125, Mini USB cable, AV cable, Mounting belt & wall mount, 3x screws & 3x dowels, 8x AA batteries, User Manual

Article-No. 4817

