


RocketRAID 2640X1

4 Channel PCI-Express x1 SAS RAID Controller



Host Adapter Architecture

- PCI-Express x1
- 4 Internal SAS/SATA 3Gb/s Device Ports
- Up to 4 SAS/SATA Hard Drives
- NCQ (Native Command Queuing)
- Low Profile

Advance RAID Features

- Support RAID 0,1,5,10 and JBOD
- Multiple RAID support
- Multiple logical drive support
- BIOS booting support
- Online Array roaming
- Automatic drive (insert / remove) detection
- Automatic RAID rebuild
- 64bit LBA support greater than 2TB per volume
- S.M.A.R.T (Early Warning System)
- TerabyteGuard™ for data protection and reliability
- Bad sector repair and remapping to reduce dropped drives

Array Monitors, Alerts and Indicators

- Hard Drive LED Indicators (Activity and Failed)
- Email Notification
- Alarm/Buzzer alerts for drive/array failure
- Enclosure Management support with I2C and SPGIO

RAID Management

- Online Capacity Expansion (OCE) and Online RAID Level Migration (ORLM)
- Quick and Background initialization for instant RAID configuration
- Write Back and Write Through support
- API library for customization
- CLI (Command Line Interface)
- Web GUI RAID management (local and remote monitoring)
- SHI (Drive analysis driven from S.M.A.R.T)

Operating System Support

- Windows (2000, XP, x64, 2003, 2008, Vista (32 and 64) bit)
- Linux (Fedora Core, Red Hat Enterprise / CentOS, SuSE)
- Mac OS X 10.4.x and above
- FreeBSD
- Linux Open Source

RocketRAID 2640X1

4 Channel PCI-Express x1 SAS RAID Controller

ROCKETRAID 2640X1 HOST ADAPTER

The RocketRAID 2640X1 is high-performance SAS RAID solutions, delivering reliability to demanding data-intensive applications such as tiered storage environments (disk-to-disk backup), security and surveillance, video editing, and digital content creation.

Support for both SAS and SATA 3Gb/s drives on the same controller maintains configuration optimization for performance based on the characteristics of SAS and SATA drives available today.

HighPoint RAID Management

HighPoint RAID Management software offers a user friendly interface to create, manage and maintain your storage solutions. Email notification and remote are some of the advance features that the RAID Management software has to offer.

COMPREHENSIVE OS SUPPORT

HighPoint offers the broadest range of support for all major operating systems to ensure OS and hardware server compatibility. Drivers are available for all major operating systems, including Windows , Linux, Mac OS X and FreeBSD. Linux Open Source driver help customers easily install and configure the RocketRAID 2640X1 controller.

PHYSICAL SPECIFICATIONS

Size: Size: (87.8mm x 64.3mm) 3.45"L x 2.53"W

EMI : FCC Part 15 Class B and CE

Thermal and Atmospheric Characteristics:

Work Temperature Range : +5°C ~+ 55°C

Relative Humidity Range : 5% ~ 60% non condensing

Storage Temperature : ~20 ~ 80°C

MTBF: 920,585 Hours

Electrical Characteristics:

PCI-e : 3.3V

Power: 5W

RocketRAID 2640X1 Specification

Host Side Interface	PCI-e x1
Device Interface	(SAS 1.0) or (SATA II / I)
Number of Channels	4 SAS Channels
Supported RAID Levels	RAID 0, 1, 5, 10, and JBOD
Operating Systems Support	Windows, Linux, Mac OS X, FreeBSD
RAID Management Tool	BIOS Web based RAID Management Software and CLI
Some Highlighted Features	Hot swap/hot spare 64bit LBA for over 2TB partition support Drive Activity/Failed LED support SMTP support for email notification OCE/ORLM Automatic RAID Rebuild Online Array Roaming

Company Information

U.S. Headquarter

Address: 1161 Cadillac Court. Milpitas, CA 95035
Phone: 1-408-942-5800
Fax: 1-408-942-5801
E-mail: sales@highpoint-tech.com
Support: support@highpoint-tech.com

HighPoint Taiwan

Address: 5F, NO.3, Swei Lane, Jungjeng Rd., Shindian City, Taipei, Taiwan 231, R.O.C.
Phone: +886-2-2218-3435
Fax: +886-2-2218-3436
E-mail: sales@highpoint-tech.com
Support: support@highpoint-tech.com

HighPoint China

Address: No. 12, Zhong Guan Cun South Rd, Beijing, China
Phone: +86-10-62130920
Fax: +86-10-68975074
E-mail: sales@highpoint-tech.cn
Support: support@highpoint-tech.cn



Product pictures and specifications are subject to change without notice.
All trademarks are the property of their respective holders.
Copyright © 2008 by HighPoint Technologies, Inc.

three limited warranty information