


# A88XM-E35 (MS-7721v6.0) m-ATX Motherboard

Supports FM2+ Socket for AMD® A- series / Athlon™ Series Processor





## **Motherboard Specification**

## **Processor Support**

■ Supports FM2+ Socket for AMD® A- series/ Athlon™ Series Processor

#### Chipset

■ AMD® A88X chipset

#### **Memory Support**

- 2 DIMMs support for DDR3-2133/ 1866/1600/1333 MHz up to 32GB max
- Supports dual channel mode

### LAN

 Supports Gb LAN 10/100/1000 Fast Ethernet by Realtek® RTL8111G

#### Audio

- Chip integrated by Realtek® ALC887
- Flexible 8-channel audio with jack sensing
- Compliant with Azalia 1.0 Spec

## SATA

■ 6 SATA 6Gb/s ports by AMD® A88X

## USB 3.0

■ 4 USB 3.0 ports by AMD® A88X (rear x 2, front x 2)

## Connectors

- Back panel
- 1 PS/2 mouse port
- 1 PS/2 keyboard port
- 1 VGA port
- 1 DVI port
- 1 HDMI port
- 4 USB 2.0 ports
- 2 USB 3.0 ports
- 1 LAN jack
- 3 flexible audio jacks
- On-Board Connectors
  - 2 USB 2.0 connectors
  - 1 USB 3.0 connector
  - 1 Front Panel Audio connector
  - 1 Serial connector
- 1 TPM Module connector
- 1 Chassis Intrusion connector
- 1 Parallel port

## Slots

- 1 PCI Express x16 slot
- 1 PCI Express x1 slot
- 1 PCI slot, Support 3.3V/ 5V PCI bus Interface

## Form Factor

■ Micro-ATX (22.6 cm X 21.6 cm)

## Feature on Focus

- M-Flash included
- USB Safeguard
- USB 3.0
- SATA 6Gb/s
- Directx 11
- Dual Graphic
- AMD Memory profile technology

## Mounting

■ 6 mounting holes

These specification is subject to change without prior notice.