

DATASHEET

Network Cabinet OFFICE 18U, 600x600 mm, RAL7035, Acoustically Insulated



General data

19" network cabinet according to DIN41494

Steel sheet housing, self-supporting, completely pre-assembled, active ventilated

Interior lined with sound-absorbing foam, attenuation ca. 8 dB

Front door with additional, high quality rubber sealing

Inside front and rear 4 x 19" profiles (2 front, 2 rear-sided), galvanised, step-less depth-adjustable

Front door full glass, 1-part (thickness 4 mm)

Front door with 1-point latch-locking

Door stop possible left or right-sided

Bottom and rear with pre-punched openings for cable entry

Roof equipped with high quality single fan with cable open end (ca. 0,3 m, without thermostat/temperature controller + cables, please order separately)

Internal earthing of all cabinet sections

Paint finish RAL7035, light grey / RAL9005, jet black

Max. load 45 kg

Protection degree IP20

Included in delivery: 1 x brush, 4 x leveling feet M8, 2 x key

Delivery in transport packaging on disposable pallet

Technical properties

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.



DATASHEET

Network Cabinet OFFICE 18U, 600x600 mm, RAL7035, Acoustically Insulated

Degree of protection	
Demountable	
Material	
Model	
Modular spacing	
Mounting level	
Surface finishing	
Type of back door	Rear wall
Type of front door	Full glass door 1-part
Type of profile rail	
Type of ventilation	Active
With backside door	
With earthing	
With front door	
With roof plate	
With sidewall	
With socket	

Available variants

ArtNr.	Bezeichnung	Color	Depth	Number of height units	Width	Height	RAL-number	Number of doors
OFF-1866GR.V1RW-AK	Network Cabinet OFFICE 18U, 600x600 mm, RAL7035, Acoustically Insulated	grey	600 mm	18 HE	600 mm	871 mm	7035	1
OFF-1866TS.V1RW-AK	Network Cabinet OFFICE 18U, 600x600 mm, RAL9005, Acoustically Insulated	black	600 mm	18 U	600 mm	871 mm	9005	1
OFF-1868TS.V1RW-AK	Network Cabinet OFFICE 18U, 600x800 mm, RAL9005, Acoustically Insulated	schwarz	800 mm	18 HE	600 mm	871 mm	9005	1

This datasheet was created automatically on 11-09-2025 . Technical changes reserved.

