

DIGITUS Industrial Gigabit PoE+ Injector 802.3 af/at

DN-651112

EAN 4016032445845



Industrial Gigabit PoE+ Injector 802.3at 60W power output, DIN rail and wall mount design,

The Digitus PoE Injector allows you to minimize cabling during installation of PoE-ready devices such as IP network cameras. Data supply and power supply to the devices is accomplished using a single Ethernet cable. This makes laying a separate power cable unnecessary and allows you to extend your network to places where there are no outlets or power cables. The Injector is fully compliant with the IEEE802.3at Ultra PoE standard and delivers an output power of 60 W.

High Power output with 60 watts

- Meets the 802.3af/at PoE standard
- 48~55 volt output voltage, 60 watts
- RJ45 LAN input
- LAN (RJ45) output, power supply via pin: 4/5(+), 7/8(-) and 3/6(+), 1/2(-)
- Cable connection: 10/100/1000 Mbps

- The output has a current limit, a short-circuit protection and an automatic terminal device detection and classification
- Power consumption: 3W max.
- Operating temperature: -40°C - 75°C
- Less than 0.3W idle consumption
- Compact, robust metal housing
- Excellent short circuit protection
- Lightning and overvoltage protection
- DIN rail (top hat rail) and wall mounting possible
- Ethernet speed: Gigabit
- PoE Power budget: 60 W
- PoE standard: IEEE802.3at (PoE+)

Package contents

- Industrial Gigabit PoE+ Injector 802.3 af/at
- Quick start guide

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	36	14.76	39.00	35.00	33.00	45,045.00
Packaging Unit Inside	1	0.41	16.50	12.50	5.00	1,031.25
Packaging Unit Single	1	0.41	16.50	12.50	5.00	1,031.25
Net single without Packaging	1	0.38	16.50	12.50	5.00	1,031.25

More images:



