
Hard drives and expansion card retainer installation


1. Remove 4 screws from expansion card retainer






User manual

www.silverstonetek.com



2. Expansion card retainer position shift (It is recommended to avoid the position of the expansion card connectors, and make sure the length of the PSU will not interfere.)



113mm

Expansion card height limitation (Please take into account the power connectors

DU

1. Height limitation with expansion card clip buckle installed

Graphics Card


2. Height limitation with expansion card clip buckle removed

3. Install 2 x 3.5" HDD on the expansion card retainer





5. Install 2.5" drives on 2.5" trays.

















4. Removing expansion card clip buckle






5. Adjust the position of the expansion card retainer according to the required

height of the interface card, then tighten the screw




Nvidia 30 series graphics card brackets installation

1. Install Nvidia 30 series graphics cards




4. Install 3 x 2.5" SSD on the expansion card retainer



3. Height limitation with expansion card retainer removed


2. Install Nvidia 30 series graphics cards bracket (slightly tighten the screws, and reserve space for the bracket to slide left and right)



Vertical orientation installation


3. Once the graphics card bracket is pushed into position, tighten the thumb screw then the graphics card screw

Note: Nvidia 30 series graphics card bracket supports graphics card length of 285mm~344mm (the total length of the graphics card must exceed the edge of the motherboard)




Install Mini Redundant PSU

1. If Mini Redundant PSU is to be installed, please first remove the ATX PSU bracket



4. If the 8th slot is to be used for expansion cards, please remove the 2.5" drive

tray as appropriate



Warranty Information

This product has a limited 1 year warranty in North America and Australia. For information on warranty periods in other regions, please contact your reseller or SilverStone authorized distributor. 本产品目的实达日起,于中国地区(不包含澳门,香港特别行政区)享有一年有限责任保固(部分产品为二年,三年或五年)。 详细保固年限请参照官方网站 https://silverstonetck.com.cn/公布之产品型号为依据。

0

0


0. 0

nty terms & co

- Product component defects or damages resulted from defective production is covered under warranty. Defects or damages with the following conditions will be fixed or replaced under SilverStone Technology's jurisdiction.t
 a) Usage in accordance with instructions provided in this manual, with no misuse, overuse, or other inappropriate actions.

- a) Usage in accordance with instruction percent percent in approximation of the percent percent in appropriate actions.
 b) Damage not caused by natural disaster (thunder, fire, earthquake, flood, salt, wind, insect, animals, etc...)
 c) Product is not disassembled, modified, or fixed. Components not disassembled or replaced.
 d) Warranty mark/stickers are not removed or broken.
 Loss or damages resulted from conditions other than ones listed above are not covered under warranty.
 2. Under warranty, SilverStone Technology's maximum liability is limited to the current market value for the product (depreciated value, excluding shipping, handling, and other fees). SilverStone Technology is not responsible for other damages or loss associated with the use of product.
- 3. Under warranty, SilverStone Technology is obligated to repair or replace its defective products. Under no circumstances will SilverStone Technology be liable for damages in connection with the sale, purchase, or use including but not limited to loss of data, loss of business, loss of profits, loss of use of the product or incidental or consequential damage whether or not foreseeable and whether or not based on breach of warranty, contract or negligence, even if SilverStone Technology has been advised of the possibility of such damages.
- 4. Warranty covers only the original purchaser through authorized SilverStone distributors and resellers and is not transferable to a second hand purchaser.
- 5. You must provide sales receipt or invoice with clear indication of purchase date to determine warranty eligibility

- 6. If a problem develops during the warranty period, please contact your retailer/reseller/SilverStone authorized distributors or SilverStone thtp://www.silverstonetek.com.
 6. If a problem develops during the warranty period, please contact your retailer/reseller/SilverStone authorized distributors or SilverStone thtp://www.silverstonetek.com.
 6. If a problem develops during the warranty period, please contact your retailer/reseller/SilverStone authorized interviews transporting) the product board or diginal purchase of the product by a dated itemized receipt; (ii) You shall bear the cost of shipping (or otherwise transporting) the product board back to you after completing the warranty service; (iii) Before you send the product, you must be issued a Return Merchandise Authorization ("RMA") number from SilverStone. Updated warranty information will be posted on SilverStone's official website.
 Please visit http://www.silverstonetek.com for the latest updates.





QQ \bigcirc Car O O0

Component restrictions

1. CPU cooler height limitation with expansion card retainer is 137mm, and 148mm without. CPU cooler is allowed to protrude the motherboard by 15mm to avoid interference with the PSU.

If hard drives are to be installed on the expansion card retainer, further deduct the height of the hard drives






2. When shifting positions of the expansion card retainer, the maximum depth

limitation for PSU is 255mm to avoid interference.

255mm ø power supply ١Ľ 0 10 0 0 C 0



Additional info & contacts

For North America	a (usasupport@silver	stonetek.com)			
SilverStone Technology in North America may repair or replace defective product with refurbished product that is not new					
functionally tested.					
Replacement produ	ct will be warranted	for remainder of the	warranty period or th	irty days, whichever	is longer. All produc
back to the place of	f purchase if it is				
within 30 days of purchase, after 30 days, customers need to initiate RMA procedure with SilverStone Technology in USA					
the "USA RMA form	n for end-users"				
form from the below	v link and follow its in	structions. http://silv	/erstonetek.com/co	ntactus.php	
For Australia only	(support@silverston	etek.com)			
Our goods come with guarantees that cannot be excluded under the Australian Consumer Law.					
You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable					
You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure doe					
major failure.					
Please refer to above "Warranty terms & conditions" for further warranty details.					
SilverStone Techno	logy Co., Ltd. 12F No	o. 168 Jiankang Rd.,	Zhonghe Dist., New	Taipei City 235 Taiv	van R.O.C. + 886-2-8
international call cha	arges apply)	-	-		
For Europe (suppo	ort.eu@silverstonet	ek.de)			
For China (suppor	t@silverstonetek.c	om.cn)			
For all other region	ns (support@silver	stonetek.com)			
					e +
有毒有害物质/元素及其化学含量表					
20/11 /2 71	铅	汞	镉	六价铬	多溴联苯
部件名称	(Pb)	(Hg)	(Cd)	(Cr(VI))	(PBB)
机壳	\cap	\bigcirc	\cap	\cap	
(金属)					
风扇		0		0	
		-			

Ο

Ο

Ο

 \bigcirc

0

 \bigcirc

本表格依据SJ/T 11364的规定编制 〇:表示该有毒有害物质在该部件所有均质材料中的含量均在GB/T 26572 规定的限量

Ο

 \bigcirc

 \bigcirc



 \bigcirc

 \bigcirc

 \bigcirc

要求以下。 ×:表示该有毒有害物质至少在该部件的某一均质材料中的含量超出GB/T 26572 规定的 限量要求。

 \bigcirc

Ο


Ο

线材

螺丝

包材


3. Install handle bar onto the flat handle bar bracket



1. Remove L-shaped handle bar brackets on both sides


2. Install Mini Redundant PSU

4. Install case feet (including case feet washers)





3. The maximum length limitation for graphics cards, front panel case fans, and radiator is 424mm



v but has been

cts should be sent

A by first downloading

e loss or damage oes not amount to a

2-8228-1238 (standard

多溴二苯醚 (PBDE) \bigcirc Ο \bigcirc Ο Ο 「品合格证 SilverStone Technology Co., Ltd.

www.silverstonetek.com

support@silverstonetek.com