


DIGITUS DisplayPort Connection Cable

AK-340100-150-S
EAN 4016032330776



Displayport connection cable, DP M/M, 15.0m, w/interlock, Full HD 1080p, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Support 1080p with 30Hz
- Max. supported Video Resolution: 1920 x 1080 p
- Supported transmission modes: RBR, HBR, HBR2
- AWG: 28
- Interlock: Snap fastener
- Connector surface: nickel-plated

- Color cable: black
- Color connector: black
- Hoods: molded
- Shielding: triple shielding
- Connector 1: DP, plug
- Connector 2: DP, plug
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- Assortment: DisplayPort Cables
- AOC - Active Optical Cable: no
- HDTV Standard: Full HD
- Length: 15 m
- Packaging: Polybag
- Wire material: CU

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	9.20	36.50	33.00	20.00	24,090.00
Packaging Unit Inside	1	0.92	7.00	22.00	28.50	4,389.00
Packaging Unit Single	1	0.92	7.00	22.00	28.50	4,389.00
Net single without Packaging	1	0.91	7.00	22.00	28.50	4,389.00

More images:

