





STEREOTVIN AUDIO WIRELESS SPEAKER

ENERMAX STEREOTWIN speakers feature BLUETOOTH CSR[®] V4.0 chipset to provide quick and seamless connectivity for true wireless stereo sound. The aluminum exterior presents a modern and stylish feel. Equipped with ENERMAX DreamBass[™] technology, STEREOTWIN delivers amazing high-definition and deep bass sound. You can enjoy high-quality wireless stereo sound any time, any where.




Features

Two STEREOTWIN speakers to create dual-channel sound effect

Single speaker of STEREOTWIN alone can generate powerful sound. Pair 2 STEREOTWIN via BLUETOOTH connection (the operational range up to 75 feet) to form left and right channel and enjoy the freedom of maximum mobility.






Superior CSR[®] V4.0 technology

Built-in advanced CSR[®] V4.0 chipset offers quick and seamless connection to smart phones, tablets or other BLUETOOTH devices, creating high-quality music streaming to amplify your listening experience.

■ DreamBass[™] technology creates loud and clear sound

With one 4 watt driver and a passive radiator, STEREOTWIN harnesses ENERMAX DreamBass[™] technology to generate rich bass sound.



Durable build

Premium aluminum housing makes the speakers sleek yet durable. The shock-absorbing rubber at the bottom keeps the speaker in place despite heavy vibration as audio is playing.





ENERMAX LED technology creates a touch of premium elegance

Easily access your music

STEREOTWIN is equipped with a 3.5mm aux input jack for line-in music play. The audio cable is included for you to enjoy your favorite music from any audio sources.





User-friendly interface

Easy access interface allows users to wirelessly access to play, pause, track forward / backward, volume +/-, and hands-free talking. Operating this speaker is simple and straightforward.

Support hands-free talking

Built-in microphone enables you to answer calls from your BLUETOOTH-enabled phones while meeting or exercising.



Model Number							
		EAS02S-BK	EAS02S-W	EAS02S-R	EAS02S-BL	EAS02S-DBK	EAS02S-DW
Amplifier	Power	4W + passive radiator					
Frequency Response		120Hz-16KHz					
Maximum Sound Level		110dB					
Signal-to-Noise Ratio		70dB					
Dimensions of Speaker unit		52 mm					
General Specifications							
Battery	Туре	Li-Po rechargeable battery					
Battery Life		8 hours					
Battery Charge Time		2 hours					
Weights		320g					
Dimensions		Ø72 mm x H85 mm					
Connectivity Specifications							
Bluetooth [®] Technology		4.2					
Bluetooth [®] Frequency Range		2.4GHz-2.48GHz					
Profile Support		HFP, A2DP, AVRCP, HSP, GAVDP, IOP					
Line of Signal Range		70 - 75 ft (actual operating distance depending upon environmental factors)					
Shipping Information							
Barcode	EAN	4713157722577	4713157722607	4713157722591	4713157722584	4713157722683	4713157722706
	UPC	816163008797	816163008827	816163008810	816163008803	816163008902	816163008926
Box Dimension		85 x 85 x 160 (mm)				190 x 115 x 110 (mm)	
Gross Weight / Unit		470 (g)				1000 (g)	
Carton Dimension		445 x 445 x 360 (mm)				570 x 470 x 260 (mm)	
Gross Weight / Carton		32 (units) / 17.1 kg				16 (units) / 17.9 kg	



© 2017 ENERMAX TECHNOLOGY CORPORATION. All rights reserved. Specifications are subject to change without notice. Content of delivery might differ in different areas or from illustrations. Some trademarks may be claimed as the property of others.