


DIGITUS Modular Patch Panel, 16-port

DN-91400**EAN 4016032280750****Modular Patch Panel, unshielded, 16-port blank, 1U, rack mount, black RAL 9005**

The Modular Patch Panel from DIGITUS® is available as 16- or 24-port version. The 1.5 mm cold rolled c-steel provides the best storage of your Keystone Modules.

- Layout Keystone Entry: Double-row
- Area of application: 483 mm (19") cabinet
- Norms: ISO/IEC 11801 3rd Ed., EN 50173-1, EIA/TIA 568-C
- General properties:
- Suitable for 483 mm (19") cabinet mounting
- Suitable for unshielded Digitus® Keystone Modules and Couplers
- Technical properties:

- Housing material: 1.5 mm SPCC cold rolled stell sheet, powder-coated
- Material standard: EN 10 130(1991), BS 1449, NFA 36/401, DIN 1623, UNI 5866, UNE 36-086, SIS, JIS G 3141, ASTM, SAE, NFA 36/401
- Physical properties:
- Operation temperature: -20° C to +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)
- Colour: Black RAL9005

Attributes

- Color: black, RAL 9005
- Ports: 16
- Units: 1

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	64	22.02	58.00	24.00	25.00	34,800.00
Packaging Unit Inside	8	2.75	56.50	10.00	7.50	4,237.50
Packaging Unit Single	1	0.34	48.50	4.30	1.50	312.83
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

Safety notes

- Protect product from moisture

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com