


# **OVERVIEW**



1. Power connector	5. Headphone / microphone combo jack (3.5mm)
2. USB 3.2 Gen 1	6. Card reader
3. HDMI 1.4b	7. USB 2.0
4. USB-C 3.2 Gen 1	



# **PERFORMANCE**

### **Processor**

#### **Processor Family**

AMD Ryzen™ 3 / 5 / 7 Processor

#### **Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency Cache		Memory Support	Processor Graphics
AMD Ryzen 3 5425U	4	4 8 2.7GHz		4.1GHz	2MB L2 / 8MB L3	DDR4-3200 AMD Radeon™ Graphics	
AMD Ryzen 5 5625U	6	12	2.3GHz	4.3GHz	3MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 5825U	8	16 2.0GHz		4.5GHz	4MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics

# **Operating System**

### **Operating System**

- Windows® 11 Home 64
- Windows 11 Home in S mode
- No operating system

### **Graphics**

#### **Graphics**

Graphics	Type	Memory	TGP	Key Features
AMD Radeon Graphics	Integrated	Shared	Shares CPU TDP	DirectX® 12

# **Monitor Support**

### **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C)

- HDMI supports up to 4K@30Hz
- USB-C supports up to 4K@60Hz

# **Chipset**

### Chipset

AMD SoC (System on Chip) platform

### **Memory**

### Max Memory[1]

- Up to 12GB (4GB soldered + 8GB SO-DIMM) DDR4-3200 offering
- Up to 16GB (8GB soldered + 8GB SO-DIMM) DDR4-3200 offering

# **Memory Slots**

One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable

### **Memory Type**

DDR4-3200

### Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

# **Storage**

#### **Storage Support**

- Model with 38Wh battery: up to two drives, 1x 2.5" HDD + 1x M.2 SSD
  - 2.5" HDD up to 1TB
  - M.2 2242 SSD up to 512GB
  - M.2 2280 SSD up to 1TB

### IdeaPad 3 17ABA7



- Model with 45Wh battery: one drive, 1x M.2 SSD
  - M.2 2242 SSD up to 512GB
  - M.2 2280 SSD up to 1TB

#### **Storage Slot**

- Model with 38Wh battery: one 2.5" drive slot + one M.2 slot
  - One 2.5" drive slot, supports 2.5" SATA HDD
  - One M.2 2280 PCle® Gen 3x4 slot, supports M.2 2242/2280 SSD
- Model with 45Wh battery: one M.2 slot
  - One M.2 2280 PCIe Gen 3x4 slot, supports M.2 2242/2280 SSD

#### Storage Type[1]

Disk Type	Interface	Offering		
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x4	128GB / 256GB		
M.2 2242 SSD	PCIe NVMe, PCIe 4.0 x4	256GB / 512GB		
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	512GB / 1TB		

#### Notes:

1. The SSD with PCI 4.0x4 is downgraded to closer to PCIe 3.0x4 due to the system slot limitation.

# **Removable Storage**

### **Optical**

. None

#### Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

### Multi-Media

### **Audio Chip**

High Definition (HD) Audio

#### **Speakers**

Stereo speakers, 1.5W x2, Dolby® Audio™

### Microphone

Dual array microphone

#### Camera

720p, with privacy shutter, fixed focus

### **Battery**

### **Battery**

- Integrated Li-Polymer 38Wh battery, supports Rapid Charge (charge up to 80% in 1hr)
- Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

### Max Battery Life[1]

• Model with 38Wh battery:

MobileMark® 2018: 8.5 hr

Local video (1080p) playback@150nits: 12.3 hr

Model with 45Wh battery:

MobileMark 2018: 10 hr

Local video (1080p) playback@150nits: 13 hr

### Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

### **Power Adapter**

### **Power Adapter**

65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz



### **DESIGN**

# **Display**

### Display[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
17.3"	HD+ (1600x900)	None	TN	250 nits	Anti- glare	16:9	600:1	60% NTSC	90°	-
17.3"	FHD (1920x1080)	None	IPS	300 nits	Anti- glare	16:9	800:1	72% NTSC	170°	-

#### **Touchscreen**

Non-touch

Notes.

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

### **Input Device**

### Keyboard

6-row, multimedia Fn keys, numeric keypad

#### **Keyboard Backlight**

No support

### **Touchpad**

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 69 x 104 mm (2.72 x 4.09 inches)

### **Mechanical**<sup>(1)</sup>

#### **Dimensions (WxDxH)**

399 x 274 x 19.9 mm (15.71 x 10.79 x 0.78 inches)

### Weight

2.2 kg (4.8 lbs)

#### **Case Color**

- Abyss blue
- · Arctic grey

#### **Surface Treatment**

Painting

#### **Case Material**

PC + ABS (top), PC + ABS (bottom)

#### Notes

1. The system dimensions and weight vary depending on configurations.

# CONNECTIVITY

#### **Network**

#### WLAN + Bluetooth®

- 802.11ac 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card

# Ports<sup>[1]</sup>

### **Standard Ports**

- 1x USB 2.0
- 1x USB 3.2 Gen 1
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery 3.0, and DisplayPort™ 1.2)

### IdeaPad 3 17ABA7



- 1x HDMI 1.4b
- · 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector

#### Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s; FireWire 400: 400 Mbit/s;

FireWire 800: 800 Mbit/s

# SECURITY & PRIVACY

# Security

### **Security Chip**

Firmware TPM 2.0 integrated in chipset

### **Fingerprint Reader**

- Touch style fingerprint reader on power button
- · No fingerprint reader

#### **BIOS Security**

- Administrator password
- Power-on password
- · Hard disk password

### **Other Security**

Camera privacy shutter

### **SERVICE**

### Warranty

### Base Warranty[1]

- 1-year depot service
- 2-year (1-yr battery) depot service

#### Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

# **ENVIRONMENTAL**

# **Operating Environment**

### Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition:  $31.3^{\circ}\text{C}$  (88°F)

### Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Δltitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:



1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

### **CERTIFICATIONS**

### **Green Certifications**

#### **Green Certifications**

- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.















ΔMDA