

EAN: 4015474179233
static.hansa.com/57942171



- öffentliche & halböffentliche Bereiche
- Einhebelmischer, Fertigmontageset
- Wandmontage für Unterputz-Einbaukörper
- Chrom
- CACHE® Strahlregler, ohne Mundstück direkt in den Armaturenauslauf geschraubt, CASCADE® Strahlregler
- Einhandbedienhebel/Griff, Hebel mit W+K-Kennzeichnung, Pinhebel
- Kürzbar, Wasserwege ohne Nickelbeschichtung
- Rosette rund

Technische Daten

Durchflusseigenschaften

Durchfluss bei 3 bar **7.8 l/min**

Technische Eigenschaften


Warmwasserversorgung **max. +80°C**
 Arbeitsdruck **0.5-10 bar**
 Projection **225 mm**
 Sicherungseinrichtung (EN1717) **AA**
 Werkstoff **Messing**



Vorschriften

EN Standard **EN 817**
 Geräuschklasse **I (ISO 3822)**

Zulassungen und Deklarationen

DVGW **DW-6512CS0518**
 ABP **P-IX 29077/IZ**





This exploded view diagram illustrates the assembly of a mechanical component, likely a pump or valve. The components are numbered as follows:

- 1**: A long, thin cylindrical shaft or rod.
- 1.1**: A small cylindrical pin or bushing.
- 1.4**: A small circular washer or spacer.
- 2**: A short, thick cylindrical component, possibly a sleeve or bushing.
- 7**: A large, flat, rectangular plate or cover.
- 7.1**: A small circular gasket or seal.
- 7.2**: A large circular flange or end plate.
- 7.3**: A smaller circular flange or end plate.
- 8.1**: A large, curved, U-shaped component, possibly a housing or bracket.
- 8.2**: A threaded bolt or screw.
- 8.3**: A small, rectangular component, possibly a seal or gasket.
- 8.4**: A complex, multi-part component, possibly a valve or actuator.

Dashed lines indicate the assembly path and alignment of the components.

	Name	Art.-Nr.
1	Hebel, 50 mm, d 7 mm	59913097
1.1	Schraube, M5x25, SW 2,5	59913099
1.4	O-Ring, d 3x1.5	59913100
1.5	Abdeckkappe	59913098
2	Abdeckhülse	59912116
7	Rosette, d 75 mm	59913246
7.2	Rosette, d 75 mm	59913240
7.3	O-Ring, 42x2	59913173
8.1	Auslauf, L=225	59913244
8.1	Auslauf, L=300	59913245
8.2	Gewindenippel, G1/2, AF12	59912144
8.3	Luftsprudler, M24x1 A, 8 l/min	59913130
8.4	Schlüssel für Luftsprudler, M24x1	59913134
N.I.	Verlängerungssatz, 20 mm	59913136