

## EUROLITE LED IP PAR 7x8W QCL Spot

Weather-proof (IP65) spotlight with 7 x 8 W LED and 4in1 QCL RGBW color mixing

Art. No.: 51914230

GTIN: 4026397669244



**List price: 248.71 €**

incl. 19% VAT.

### Features:

- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - Strobe effect
  - Direct color selection for 25 preset colors
  - The device is cooled by passive convection cooling
  - Control via DMX; stand-alone; IR remote control
  - Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
  - Flicker-free
  - With a beam angle of 15°
  - With double bracket
  - LCD display
  - Mains input and output for power linking up to 8 units
  - Suitable for outdoor use IP65
  - With pressure compensation membrane
  - For application areas such as: Installation; stage; rental; architecture
  - Silent operation
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397669244

Weight: 4,60 kg

Length: 0.33 m

Width: 0.30 m

Height: 0.19 m

## Technical specifications:

|                          |                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                       |
| Power consumption:       | 55 W                                                                                                                                                         |
| IP classification:       | IP65                                                                                                                                                         |
| Power connection:        | Mains input via IP T-Con (M) mounting version power supply cord with safety plug                                                                             |
| Power output:            | IP T-Con (F) mounting version                                                                                                                                |
| Lamp type:               | LED lamp                                                                                                                                                     |
| LED type:                | 7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)                                                                                                      |
| Flash rate:              | 0 - 20 Hz                                                                                                                                                    |
| DMX channels:            | 3; 4; 5; 6; 10                                                                                                                                               |
| DMX input:               | 1 x 3-pin XLR (M) mounting version IP                                                                                                                        |
| DMX output:              | 1 x 3-pin XLR (F) mounting version IP                                                                                                                        |
| Cooling:                 | Passive convection cooling                                                                                                                                   |
| Control:                 | DMX; stand-alone; IR remote control                                                                                                                          |
| Preprogrammed in:        | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:              | Flicker-free                                                                                                                                                 |
| Beam angle:              | 15°                                                                                                                                                          |
| Beam angle (1/2 peak):   | 15°                                                                                                                                                          |
| Housing color:           | Black                                                                                                                                                        |
| Attachment system:       | Double bracket                                                                                                                                               |
| Display type:            | LCD display                                                                                                                                                  |
| Material:                | Aluminum casting                                                                                                                                             |
| Dimensions:              | Width: 25,5 cm<br>Depth: 15,3 cm<br>Height: 28,1 cm                                                                                                          |
| Weight:                  | 4,07 kg                                                                                                                                                      |
| Noise classification:    | Class 0 (no noise at all)                                                                                                                                    |
| Photobiological safety:  | Risk Group 0                                                                                                                                                 |
| Mounting bracket         |                                                                                                                                                              |
| Diameter mounting holes: | 3 x Ø11mm                                                                                                                                                    |
| Material:                | Metal, 2,5 mm                                                                                                                                                |
| Power cord               |                                                                                                                                                              |
| Cable construction:      | 3 x 1,0 mm² H05RN-F                                                                                                                                          |
| Cable length:            | Approx. 1,2 m                                                                                                                                                |
| Remote control           |                                                                                                                                                              |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                      |
| Legal specifications     |                                                                                                                                                              |
| Special product:         | Not designed for household room illumination                                                                                                                 |

Intended use:

Show effect lighting