



Smooth retraction with CSR




Easy Install with metal brackets



16:10 16:9 4:3 1:1

- Matte White**
Viewing Angle: 120°
Gain: 1.0
- High Contrast**
Viewing Angle: 100°
Gain: 1.1
- Datalux**
Viewing Angle: 70°
Gain: 1.5



Hapro CSR

- Professional quality manual projection screen with the reliable Controlled Screen Return, available in various aspect ratios and screen surfaces.
- The special Controlled Screen Return spring mechanism for the Hapro CSR is very strong. It retracts the projection surface quickly for the first part and then slows down to roll into the case smoothly.
- The Hapro CSR needs to be fully extracted. There are no intermediate stopping positions.
- Easy to mount onto a wall or ceiling thanks to the Easy Install system.
- The case and the projection screen surface can be made to exactly the right size and the case and slat bar are available in any colour for optimal integration into any interior.
- The triangular slat bar retracts into the case for a clean finish.

Available dimensions

Minimum width: 200 cm |
Maximum width: | 340 cm

Other options

- Without border

Accessories

- Pull Rod
- BrightSight for safely cleaning the projection surface
- More on page 58

NOT SUITABLE FOR ULTRA SHORT THROW PROJECTION



Dimensions and product codes on **100**



Aluminium case




Round slat bar



16:10 16:9 4:3 1:1

- Matte White**
Viewing Angle: 120°
Gain: 1.0



Dynamic CSR

- High quality manual projection screen featuring an anodised aluminium case and grey end caps complete with Controlled Screen Return.
- The Dynamic CSR (Controlled Screen Return) allows for the projection screen surface to retract gently into the case in a smooth and controlled manner.
- The Dynamic CSR needs to be fully extracted. There are no intermediate stopping positions.
- Easy to mount onto a wall or ceiling thanks to the supplied brackets which can be positioned laterally.
- The case and the projection screen surface can be made to exactly the right size.
- The Video (4:3), HDTV (16:9) and Wide (16:10) formats feature a 5 cm black border all around. The square (1:1) format does not include borders.

Available dimensions

Minimum width: 180 cm |
Maximum width: | 240 cm

Accessories

- Pull Rod
- BrightSight for safely cleaning the projection surface
- More on page 58

NOT SUITABLE FOR ULTRA SHORT THROW PROJECTION



Dimensions and product codes on **100**