



Delock Adapter DVI male > DisplayPort 1.2 female black

Description

This adapter by Delock can be used to connect e.g. a DisplayPort monitor to a free DVI interface of the system.



Specification

- Connectors:
 - 1 x DVI 24+1 male with screws
 - 1 x USB Type-A male (power supply)
 - 1 x DisplayPort 20 pin female
- Chipset: STDP2600
- DVI-D (Single Link), VGA not wired
- DisplayPort 1.2 specification
- Signal direction: DVI input > DisplayPort output
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports HDCP 1.4
- Plug & Play
- Power consumption: ca. 70 mW
- Colour: black
- Cable length incl. connectors: ca. 30 cm
- OS independent, no driver installation necessary

System requirements

- One free DVI 24+1 female
- A free USB Type-A female port
- Monitor with a free DisplayPort interface
- DisplayPort connection cables

Package content

- DVI to DisplayPort Adapter

Item no. 62596

EAN: 4043619625963

Country of origin: China

Package: Retail Box



Images





General	
Function:	Plug & Play
Specification:	DVI-D (Single Link)
	DisplayPort 1.2
	HDCP 1.4
Supported operating system:	OS independent, no driver installation necessary
Interface	
Output:	1 x DisplayPort 20 pin female
Input:	1 x DVI 24+1 male with screws
	1 x USB Type-A male (power supply)
Technical characteristics	
Chipset:	STDP2600
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Maximum power consumption:	70 mW
Signal transmission:	video
	audio
Physical characteristics	
Cable length incl. connector:	13.5 cm
Colour:	black