



Delock USB Condenser Microphone Omnidirectional for Conferences

Description

This table microphone by Delock is suitable for use in conferences.

Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Touch mute button & status LED

The touch mute button quickly mutes the microphone. The LED is red when muted and green when recording.

Headphone output

The microphone has a 3.5 mm stereo jack output for connecting headphones or speakers.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

**1,5 m**

Specification

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -16 dB +/- 3 dB
- Frequency range: 100 Hz - 10 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 65 dB
- Mute-Button
- Status LED
- Cable length: ca. 1.5 m
- Colour: black
- Dimensions (Ø x H): ca. 75 x 19 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Item no. 20672

EAN: 4043619206728

Country of origin: China

Package: • Retail Box



Images



operational

muted



General	
Function:	Plug & Play
Supported operating system:	Chrome OS
	Mac OS 10.9 or above
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8 32-bit
	Windows 8 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 4.4 or above
LED indicator:	1 x
Interface	
connector:	1 x USB 2.0 Type-A male
Technical characteristics	
Frequency range:	100 Hz - 10 kHz
Voltage:	USB bus powered
Sensibility:	-16 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. 65 dB
Directivity:	omnidirectional
Physical characteristics	
Cable length:	1.5 m
Diameter:	75 mm
Height:	19 mm
LED colour:	red
	green