



Philips Signage Solutions
D-Line Display

98"

UHD (3840 x 2160)
500cd/m²

SignageSolutions



98BDL4510D

Say more

Smart, fast 24/7 display.

Amaze your guests with a smarter, faster, signage display. With integrated WiFi and designed for running Android apps, it's the next evolution in signage solutions.

Brilliant picture. Blazing processor speed.

- Place in landscape or portrait orientation
- 4K UHD. Rich, deep images. Stunning contrast
- IPS panel: rich color consistency from every angle

Operational flexibility

- SmartPower for energy saving

Effortless setup. Total control.

- Schedule what you want, when you want with SmartPlayer
- Operate, monitor and maintain with CMND & Control

Cost-effective system solution

- FailOver ensures content is always playing
- Energy-saving automatic backlight control


PHILIPS

D-Line Display
98" UHD (3840 x 2160), 500cd/m²

98BDL4510D/00


Highlights

FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

CMND & Control



Run your display network over a local (LAN) connection. CMND & Control allows you to

perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

SmartPlayer



Turn your USB into a true cost effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on screen menu, and enjoy your own created playlists anytime, anywhere.

Specifications

Picture/Display

- Diagonal screen size: 97.5 inch / 247.7 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @60Hz
- Brightness: 500 cd/m²
- Contrast ratio (typical): 1300:1
- Dynamic contrast ratio: 500,000:1
- Aspect ratio: 16:9
- Response time (typical): 8 ms
- Pixel pitch: TBD
- Display colors: 1.07 G Billion
- Viewing angle (H / V): 178 / 178 degree
- Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, 3D MA deinterlacing, Dynamic contrast enhancement, Progressive scan
- Panel technology: IPS

Connectivity

- Video input: Display Port 1.2 (x1), DVI-I (x 1), HDMI 2.0 (x3), USB 2.0 (x2)
- Video output: DisplayPort 1.2 (x1), HDMI 2.0 (x1)
- Audio input: 3.5 mm jack
- Audio output: 3.5mm jack
- External control: RJ45, IR (in/out) 3.5 mm jack, RS232C (in/out) 2.5 mm jack
- Other connections: OPS

Supported Display Resolution

• Computer formats

Resolution	Refresh rate
1920 x 1080	60Hz
1280 x 1024	60Hz
1024 x 768	60Hz
1280 x 720	60Hz
1440 x 900	60 Hz
1600 x 900	60Hz
1680 x 1050	60Hz
3840 x 2160	30, 60Hz
640 x 480	60Hz
800 x 600	60Hz

• Video formats

Resolution	Refresh rate
1080p	50, 60Hz
1080i	50, 60Hz
2160p	24, 30, 60Hz
480i	60Hz
480p	60Hz
576i	50Hz

576p	50Hz
720p	50,60 Hz

Dimensions

- Set dimensions (W x H x D): 2193.2 x 1248.2 x 87.9 (@Wall mount)/ 97.9 (@Handle) mm
- Set dimensions in inch (W x H x D): 86.35 x 49.14 x 3.46 inch(wall mount)/3.85 (@Handle) inch
- Bezel width: 16.0 mm (Even bezel)
- Product weight (lb): 199.52 lb
- Product weight: 90.5 kg
- VESA Mount: 800(H)X400(V) mm, M8

Convenience

- Placement: Landscape (24/7), Portrait (24/7)
- Keyboard control: Hidden, Lockable
- Signal loop through: IR Loophrough, DisplayPort, HDMI, RS232
- Network controllable: RJ45, RS232
- Energy saving functions: Smart Power
- Screen saving functions: Pixel Shift, Low Bright

Power

- Standby power consumption: <0.5 W
- Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz
- Consumption (Typical): TBD W
- Consumption (Max): TBD

Operating conditions

- Temperature range (operation): 0 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- Altitude: 0 ~ 3000 m
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20 - 80% RH (No condensation)
- Humidity range (storage) [RH]: 5 - 95% RH (No condensation)

Sound

- Built-in speakers: 2 x 10W RMS

Accessories

- Included accessories: Quick start guide, RS232 cable, AC Power Cord, IR sensor cable (1.8M), Remote Control & AAA Batteries
- Included Accessories: RS232 daisy-chain cable, Philips logo (x1), Screws, USB Cover (x1), AC


Switch Cover

Multimedia Applications

- USB Playback Audio: AAC, HEAAC, MPEG
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Video: MPEG, H.263, H.264, H.265, VP8

Miscellaneous

- On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Regulatory approvals: CE, RoHS, BSMI, CB, CCC, CU, EMF, EnergyStar 8.0, ETL, FCC, Class A, PSB, VCCI
- Warranty: 3 year warranty



Issue date 2021-05-26

Version: 1.0.1

12 NC: 8670 001 68887
EAN: 87 12581 76909 3

© 2021 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips N.V.
or their respective owners.

www.philips.com