Warranty Information

This product has a limited 1 year warranty in North America and Australia.
For information on warranty periods in other regions, please contact your reseller or SilverStone authorized distributor.
本产品自购买之日起，于中国地区（不包含澳门，香港特别行政区）享有一年有限责任保固（部分产品为二年，三年或五年）。
详细保固年限请参照官方网站 https://silverstonetek.com.cn/ 公布之产品型号为依据。

Warranty terms & conditions

1. Product component defects or damages resulted from defective production is covered under warranty. Defects or damages with the following conditions will be fixed or replaced under SilverStone Technology's jurisdiction.
a) Usage in accordance with instructions provided in this manual, with no misuse, overuse, or other inappropriate actions.
b) Damage not caused by natural disaster (thunder, fire, earthquake, flood, salt, wind, insect, animals, etc…)
c) Product is not disassembled, modified, or fixed. Components not disassembled or replaced.
d) Warranty mark/stickers are not removed or broken.
Loss or damages resulted from conditions other than ones listed above are not covered under warranty.

2. Under warranty, SilverStone Technology's maximum liability is limited to the current market value for the product (depreciated value, excluding shipping, handling, and other fees). SilverStone Technology is not responsible for other damages or loss associated with the use of product.

3. Under warranty, SilverStone Technology is obligated to repair or replace its defective products. Under no circumstances will SilverStone Technology be liable for damages in connection with the sale, purchase, or use including but not limited to loss of data, loss of business, loss of profits, loss of use of the product or incidental or consequential damage whether or not foreseeable and whether or not based on breach of warranty, contract or negligence, even if SilverStone Technology has been advised of the possibility of such damages.

4. Warranty covers only the original purchaser through authorized SilverStone distributors and resellers and is not transferable to a second hand purchaser.

5. You must provide sales receipt or invoice with clear indication of purchase date to determine warranty eligibility.

6. If a problem develops during the warranty period, please contact your retailer/reseller/SilverStone authorized distributors or SilverStone **http://www.silverstonetek.com**.
Please note that: (i) You must provide proof of original purchase of the product by a dated itemized receipt; (ii) You shall bear the cost of shipping (or otherwise transporting) the product to SilverStone authorized distributors. SilverStone authorized distributors will bear the cost of shipping (or otherwise transporting) the product back to you after completing the warranty service; (iii) Before you send the product, you must be issued a Return Merchandise Authorization ("RMA") number from SilverStone. Updated warranty information will be posted on SilverStone's official website.
Please visit **http://www.silverstonetek.com** for the latest updates.

Additional info & contacts

For North America (usasupport@silverstonetek.com)
SilverStone Technology in North America may repair or replace defective product with refurbished product that is not new but has been functionally tested.
Replacement product will be warranted for remainder of the warranty period or thirty days, whichever is longer.
All products should be sent back to the place of purchase if it is within 30 days of purchase, after 30 days, customers need to initiate RMA procedure with SilverStone Technology in USA by first downloading the "USA RMA form for end-users" form from the below link and follow its instructions.
http://silverstonetek.com/contactus.php

For Australia only (support@silverstonetek.com)
Our goods come with guarantees that cannot be excluded under the Australian Consumer Law.
You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage.
You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.
Please refer to above "Warranty terms & conditions" for further warranty details.

SilverStone Technology Co., Ltd. 12F No. 168 Jiankang Rd., Zhonghe Dist., New Taipei City 235 Taiwan R.O.C.
+ 886-2-8228-1238 (standard international call charges apply)

For Europe (support.eu@silverstonetek.de)
For China (support@silverstonetek.com.cn)
For all other regions (support@silverstonetek.com)

有毒有害物质/元素及其化学含量表

部件名称	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴二苯醚 (PBDE)
外壳 (金属)	○	○	○	○	○	○
电子卡	○	○	○	○	○	○
螺丝	○	○	○	○	○	○
包材	○	○	○	○	○	○

本表格依据 SJ/T 11364 的规定编制。
○：表示该有害物质在该部件所有均质材料中的含量均在 GB/T 26572 规定的限量要求以下。
—：表示该有害物质至少在该部件的某一均质材料中的含量超出 GB/T 26572 规定的限量要求。且该限用物質為排除項目

产品合格证
检验员：检01
生产日期：见产品条码

NO.G11235760

Please refer to SilverStone website for latest specifications updates.

SILVERSTONE®
Designing Inspiration

MS10



M.2 SATA external enclosure with USB 3.1 Gen 2

Supports 2242, 2260 or 2280 form factors of B key M.2 SATA SSD
All aluminum exterior with small, pocketable design
Supports USB 3.1 Gen 2 interface up to 10Gb/s super speed transfer rate
Supports USB Attached SCSI Protocol (UASP) function
Includes write protect function

www.silverstonetek.com

Introduction

To take advantage of increased popularity of M.2 SSD drives, SilverStone created the MS10, a robust and pocketable M.2 SATA external enclosure. It is designed to support a M.2 SATA SSD up to 80mm so users can install either newly-purchased or repurposed M.2 SATA SSDs from laptops into the MS10 to make a high-speed USB flash drive. To make the most efficient use of M.2 SATA SSD, it also has USB 3.1 Gen 2 interface for up to 10Gb/s super speed transfer rate, providing fast reading and writing compatibility. Lastly, the MS10 is designed to work without additional driver installation, so it can be carried anywhere conveniently and be used on nearly any PCs.

Specifications

Model No.	SST-MS10C
Color	Charcoal
Material	Aluminum
Data transfer rate	USB 3.1 Gen 2 up to 10Gbps (Compatible with USB 3.0/2.0 /1.1)
Connector	USB Type-C
Controller	JMicron JMS580
LED indicator	Solid White: Powered Blinking White: Reading / writing Solid Red: Powered (write-protection mode) Blinking Red: Reading (write-protection mode)
Support type of M.2 SSD	B Key SATA Type M.2 SSD x 1 Support 22 x 42 mm, 22 x 60 mm or 22 x 80 mm size
Operating system support	Microsoft Windows 10/8.1/8/7 (32bit/64bit) or future release version Mac 10.7 or future release versions
Net weight	59g
Dimension	35 mm (W) x 11 mm (H) x 104 mm (D) 1.38" (W) x 0.43" (H) x 4.09" (D)

* If you wish to use MS10 in write-protection mode, please disconnect it from computer first before flipping the switch to enable write-protection.

Installation

1 Take out the PCB



DEUTSCH

Leiterplatte herausnehmen

FRANÇAIS

Retirez le circuit imprimé

ESPAÑOL

Quite el PCB

ITALIANO

Estrarre la PCB

ไทย

น่า PCB ออกมา

繁體中文

拿出PCB

簡体中文

拿出PCB

日 本 語

PCBを取り出します


한 국 어

PCB를 꺼내십시오

РУССКИЙ

Выньте печатную плату

2 Secure screws to suitable mounting hole depending on the length of M.2 SATA SSD used



DEUTSCH

Schrauben je nach Länge der verwendeten M.2-SATA-SSD in einem geeigneten Montageloch sichern

FRANÇAIS

Fixez les vis dans les trous de montage adaptés en fonction de la longueur du SSD SATA M.2 utilisé

ESPAÑOL

Fije los tornillos al agujero de montaje adecuado dependiendo de la longitud del SSD SATA M.2 usado

ITALIANO

Fissare le viti ad un foro di montaggio adeguato in base alla lunghezza dell'SSD SATA M.2 utilizzato

ไทย

ติดตั้ง M.2 SATA SSD และยึดน็อตสกรูผ่านแหวนด้วยสกรู A เข้ากับรูติดตั้งที่เข้ากัน ขึ้นอยู่กับความยาวของ M.2 SATA SSD ที่ใช้

繁體中文

根據M.2 SATA SSD的長度，鎖固螺絲到合適的安裝孔上

簡体中文

根据M.2 SATA SSD的长度，锁固螺丝到合适的安装孔上

日 本 語

使用するM.2 SATA SSDの長さに応じて、適合する穴にネジで固定します


한 국 어

사용된 M.2 SATA SSD의 길이에 따라 적합한 장착 구멍에 나사를 고정합니다

РУССКИЙ

Закрепите винты в соответствующем монтажном отверстии в зависимости от длины используемого M.2 SATA SSD

3 Place the assembled MS10 PCB back into the enclosure



DEUTSCH

Montierte MS10-Leiterplatte im Gehäuse platzieren

FRANÇAIS

Remettez le circuit imprimé MS10 assemblé dans le boîtier

ESPAÑOL

Coloque el PCB de la MS10 de nuevo en la carcasa

ITALIANO

Riporre la PCB MS10 montata nel box

ไทย

ติดตั้ง MS10 PCB ที่ประกอบแล้วกลับลงในกล่อง

繁體中文

放置已安裝好的MS10 PCB回到MS10外接盒中

簡体中文

放置已安装好的MS10 PCB回到MS10外接盒中

日 本 語

組み上がったMS10 PCBをエンクロージャーに戻します

한 국 어

인클로저에 조립된 MS10 PCB를 삽입합니다

РУССКИЙ

Установите собранную печатную плату MS10 обратно в корпус

4 Secure side cover to the enclosure with screws to finish installation



DEUTSCH

Zum Abschließen der Installation seite Abdeckung mit Schrauben am Gehäuse sichern

FRANÇAIS

Fixez le couvercle côté sur le boîtier avec les vis pour terminer l'installation

ESPAÑOL

Fije la cubierta lado a la carcasa con los tornillos para finalizar la instalación

ITALIANO

Fissare la copertura lato al box con viti per terminare l'installazione

ไทย

แนบด้านข้างเข้ากับกล่องด้วยสกรู เพื่อทำการติดตั้งให้เสร็จ

繁體中文

蓋上側蓋，鎖固螺絲完成安裝

簡体中文

盖上侧盖，锁固螺丝完成安装

日 本 語

ネジで側部カバーをエンクロージャーに取り付けると、インストール完了です

한 국 어

스크류로 인클로저 측면 커버를 잠근 후, 설치를 마무리 합니다

РУССКИЙ

Закрепите бок крышку к корпусу с помощью винтов для завершения установки