

Version: 04.01.12

Standards	Ethernet specifications IEEE 802.3, IEEE 802.3x, IEEE 802.3u, Auto MDI / X HomePlug AV
Protocols	CSMA/CA over power supply grid
Transmission speed	200 Mbps
Transmission method	asynchronous
Modulation	OFDM - 1155 carriers, 1024/256/64-QAM, QPSK, BPSK
Data path	Ethernet <-> power supply grid
Range	300 m
Security	128-bit AES encryption over power supply grid (enabled at the touch of a button)
LEDs	▪ Power ▪ Ethernet (Link/Act) ▪ dLAN (Link/Act/quality)
Socket / connector	DE, NL, ES, PT, AT, SE, FI, NO, GR, HU, LU: Type F (CEE 7/4) / Type F (CEE 7/4) FR, BE, PL: Type E (CEE 7/7) / Type E + F (CEE 7/7 + CEE 7/4) UK, CY: Type G (BS 1363) / Type G (BS 1363) CH: Type J (SEV 1011) / Type J (SEV 1011)
Power output at integrated socket	230 V / 16 A maximum
Device port	Ethernet RJ45
Power consumption	0.1 A maximum: ▪ Maximum: 4.3 W ▪ Typical: 3.1 W ▪ Stand-by: 0.3 W
Power supply	AC 230V 50/60Hz
Damping filter	2 – 30 MHz
Filter characteristics	-22 dB to -45 dB
Temperature	Storage: -25°C – 70°C Operation: 0°C – 35°C
Weight	245 g
Dimensions	130 x 66 x 42 mm (height x width x depth)
Ambient conditions	10–90% humidity (non-condensing)
System requirements	Ethernet interface
Operating systems	Windows® XP _{32-bit} , Windows® Vista _{32/64-bit} , Windows® 7 _{32/64bit} , Linux®, Mac OS® X and all operating systems with TCP/IP support
Certifications	CE-compliant in accordance with the technical requirements of all EU countries and Switzerland: EN 55022 :2006, EN 50412-2-1 :2006, EN 60950-1:2006



dLAN[®] 200 AVplus Starter Kit

Version: 04.01.12

Sales information

Article number	01372 (DE,AT), 01373 (FR), 01374 (UK), 01370 (BE,PL,CZ,SK), 09014 (NL,ES,PT), 01371 (CH), 09015 (EU)
EAN-Code	4250059613720 (DE,AT), 4250059613737 (FR), 4250059613744 (UK), 4250059613706 (BE,PL,CZ,SK), 4250059690141 (NL,ES,PT), 4250059613713 (CH), 4250059690158 (EU)
Warranty	3 years
Service & Support	Phone and e-mail support. Please see the included support flyer or the devolo website for telephone numbers and e-mail addresses.
Design	Plastic wallplug housing
Weight	850 g
Package dimensions	188,5 x 231 x 78,5 mm (height x width x depth)
Accessories	- Documentation: printed installation guide 2 Ethernet cable RJ45-RJ45 - CD-ROM: PDF manual, Configuration software for Windows[®] XP_{32-bit}, Windows[®] Vista_{32/64-bit}, Windows[®] 7_{32/64bit}, Linux[®], Mac OS[®] X Additional software: devolo Informer

WEEE additional information

Weight WEEE	620 g
Paper (Green Dot)	180 g
Plastic (Green Dot)	11 g
Other (Green Dot)	0,4 g

© 2011 devolo AG, Germany. All rights reserved.
Specifications are subject to change without notice.