

Delock External Gaming Enclosure for M.2 NVMe PCIe SSD with SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female and RGB LED illumination

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280, 2260 and 2242 format, it can be connected via USB to the PC or laptop. The robust **metal housing with cooling fins** ensures an optimum temperature of the memory.

SuperSpeed USB 20 Gbps

The enclosure allows a **data transfer rate of 20 Gbps** on the USB-C™ port.

Gaming style

The elegant design of the Delock enclosure is a perfect match for a gaming PC and the colour gradient **RGB LED lighting** on the top is a real eye-catcher.

Additional power connector

A power supply can also be connected to the DC jack if an M.2 SSD with particularly high power requirement is installed and the power supply via the USB port is not sufficient.

Note

There is no support for SATA M.2 SSD.



Item no. 42015

EAN: 4043619420155

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - external:
 - 1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female
 - 1 x 12 V DC 5.5 x 2.5 mm jack (optional for power supply)
 - internal:
 - 1 x 67 pin M.2 key M slot
- Chipset: Asmedia ASM2364
- Supports M.2 modules in format 2280, 2260 and 2242 with key M or key B+M based

- on PCIe (NVMe)
 - Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
 - Supports NVM Express (NVMe)
 - Data transfer rate up to 20 Gbps
 - RGB LED with automatically colour gradient
 - LED indicator for access
 - Metal housing
 - Dimensions (LxWxH): ca. 126 x 57 x 16 mm
 - Hot Plug, Plug & Play
-

System requirements

- Android 11.0 or above
 - Chrome OS 91.0 or above
 - Linux Kernel 5.11 or above
 - Mac OS 11.6 or above
 - Windows 8.1/8.1-64/10/10-64/11
 - iPad Air (4th Generation) or above
 - iPad Pro (3rd Generation) or above
 - PlayStation®5
 - Surface Pro 7
 - Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port or
 - A free USB Type-A port
-

Package content

- External enclosure M.2
- Cable USB-C™ male to USB-C™ male (with adapter to USB Type-A male), length ca. 30 cm
- Screwdriver
- 2 x rubber nipple
- User manual

Images



General

Supported operating system:	Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Linux Kernel 5.11 or above PlayStation®5 Android 11.0 or above Chrome OS 91.0 or above Mac OS 11.6 or above
Supported module:	M.2 modules in format 2280, 2260 and 2242 with key M or key B+M based on PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	1 x DC jack 1 x USB 20 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key M slot

Technical characteristics

Chipset:	Asmedia ASM2364
Data transfer rate:	20 Gbps

Physical characteristics

Housing material:	Aluminium
Cable length:	30 cm
Length:	126 mm
Width:	57 mm

Height:	16 mm
Colour:	grey

Herstellerinformation	
Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de