



47703522



IP55

SCHUKO socket outlet 2gang vertical with hinged cover surface-mounted Berker W.1, polar white matt

Technical features

Architecture

Design	according to DIN 49440
--------	------------------------

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- with hinged cover that falls back, manual clip-in
- Complete housing

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	thermoplastic
Surface appearance	matt

Installation, mounting

- for vertical mounting
- for screw fastening

Connection

Conductor cross-section	1 ... 2,5 mm ²
Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
- with two clip-in places for Wago 2-wire connection terminals in the housing floor - with Wago clip-in 2-wire connection terminal for wiring - with plug-in terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
IK protection code against mechanical impacts	05
- without enhanced contact protection	

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK