

A feast for your eyes

Fujitsu Superior Displays (P-Line)



Superior



Features	P34-9 US/UE	P27-8 TS UHD	P2410 TE
Size	34.1 in (86.7 cm)	27 in (68.5 cm)	24.1 in (61.13 cm)
Aspect Ratio	21:9	16:9	16:9
Native Resolution	3440 x 1440	3840 x 2160	1920 x 1080
USB (Downstream)	2 x USB 3.2 Gen1 (Type A)	4 x USB 3.2 Gen1	2 x USB 3.2 Gen1 (Type A)
USB (Side Contacts)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)		1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)
USB (Upstream)	1 x USB Type C, 1 x USB 3.2 Gen1 Type B	1 x USB 3.2 Gen1	1 x USB Type C, 1 x USB 3.2 Gen1 Type B
Interfaces	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 2 x HDMI 2.0 1 x DisplayPort out for DaisyChain (MST)	1 x DisplayPort, 1 x Mini DisplayPort, 2 x HDMI 2.0	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 1 x HDMI 1 x DisplayPort out for DaisyChain (MST)
Stand Type	5-in-1	5-in-1	6-in-1
Height adjustment range	150 mm	130 mm	150 mm
Special Features	Color coverage 98% DCI P3, HDR 400, KVM Switch, RJ 45 LAN 1 Gbit/s, USB Type - C Port Replicator, Power delivery 65 W, AMD Freesync, AIO mode	Picture in picture function, sensor keys and cable clip	Low blue light panel for retina protection, right handed USB hub, KVM Switch, RJ 45 LAN 1 Gbit/s, USB Type - C Port Replicator, Power delivery 95 W
Data Sheet	US: Link UE: Link	Link	Link
Product Page	US: Link UE: Link	Link	Link

P-Line

P-Line Superior Displays are your choice for an uncompromising modern workplace, with a wide range of technical functions and P-Line fittings.

- Frameless In-Plane-Switching (IPS) panels with 100% coverage up to 138% sRGB color space and up to 98% DCI P3 for maximum visual pleasure
 - Pre-calibrated for best picture quality
 - High-precision color calibration $\Delta E \leq 2$
- DICOM compatible greyscale standard preset for clinical review applications
- Ergonomics (6-in-1 stand base): User can tilt, swivel, adjust height and rotate monitor in a wide range to get the optimal posture for long working days. The cable guide and appliance for PC backpack enable a complete workspace solution.
- Built-in Sensors: Assist workplace security with presence detection and reduced eyestrain by adjusting settings optimal with Auto Brightness Control (ABC). On top these functions increase energy efficiency
- Audio: Built-in speakers (2x2W), headphone connectors
- USB Type - C Docking: With 65W or 95W charging, DP Alternate Mode, KVM functions and 1 Gbit LAN connection
- DisplayView™ software: Monitor configurat on by mouse click, release of split-screen and multi-monitor functions. Best UXperience.

A feast for your eyes

Fujitsu Superior Displays (P-Line)

Superior

Features			
Size	23.8 in (60.5 cm)	24.1 in (61.3 cm)	24.1 in (61.3 cm)
Aspect Ratio	16:9	16:10	16:10
Native Resolution	1920 x 1080	1920 x 1200	1920 x 1200
USB (Downstream)	2 x USB 3.2 Gen1 (Type A)	2 x USB 3.2 Gen1 (Type A)	2 x USB 3.2 Gen1 (Type A)
USB (Side Contacts)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)
USB (Upstream)	1 x USB Type C, 1 x USB 3.2 Gen1 Type B	1 x USB Type C, 1 x USB 3.2 Gen1 Type B	1 x USB Type C, 1 x USB 3.2 Gen1 Type B
Interfaces	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 1 x HDMI 2.0, 1 x DisplayPort out for DaisyChain (MST)	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 1 x HDMI 2.0, 1 x DisplayPort out for DaisyChain (MST)	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 1 x HDMI 2.0, 1 x DisplayPort out for DaisyChain (MST)
Stand Type	6-in-1	6-in-1	6-in-1
Height adjustment range	150 mm	150 mm	150 mm
Special Features	Microsoft Windows HELLO compatible webcam, Low blue light panel for retina protection, webcam, right handed USB hub, KVM Switch, RJ 45 LAN 1 Gbit/s, USB Type - C Port Replicator, Power delivery 95 W	Microsoft Windows HELLO compatible webcam, Low blue light panel for retina protection, webcam, right handed USB hub, KVM Switch, RJ 45 LAN 1 Gbit/s, USB Type - C Port Replicator, Power delivery 95 W	Low blue light panel for retina protection, webcam, right handed USB hub, KVM Switch, RJ 45 LAN 1 Gbit/s, USB Type - C Port Replicator, Power delivery 95 W
Data Sheet	Link	Link	WE: Link WS: Link
Product Page	Link	Link	WE: Link WS: Link

P-Line

P-Line Superior Displays are your choice for an uncompromising modern workplace, with a wide range of technical functions and P-Line fittings.

- Frameless In-Plane-Switching (IPS) panels with 100% coverage up to 138% sRGB color space and up to 98% DCI P3 for maximum visual pleasure
- Pre-calibrated for best picture quality
 - High-precision color calibration $\Delta E \leq 2$
 - DICOM compatible greyscale standard preset for clinical review applications
- Ergonomics (6-in-1 stand base): User can tilt, swivel, adjust height and rotate monitor in a wide range to get the optimal posture for long working days. The cable guide and appliance for PC backpack enable a complete workspace solution.
- Built-in sensors: Assist workplace security with presence detection and reduced eyestrain by adjusting settings optimal with Auto Brightness Control (ABC). On top these functions increase energy efficiency
- Audio: Built-in speakers(2x2W), headphone connectors
- USB Type - C Docking: With 65W or 95W charging, DP Alternate Mode, KVM functions and 1 Gbit LAN connection
- DisplayView™ software: Monitor configuration by mouse click, release of split-screen and multi-monitor functions. Best UXperience.

A feast for your eyes

Fujitsu Superior Displays (P-Line)

Superior



Features	P27-9 TE/TS QHD	P24-8 WE Neo	P24-9 TE
Size	27 in (68.5 cm)	24 in (61 cm)	23.8 in (60.5 cm)
Aspect Ratio	16:9	16:10	16:9
Native Resolution	2560 x 1440	1920 x 1200	1920 x 1080
USB (Downstream)	2 x USB 3.2 Gen1 (Type A)	4 x USB 3.2 Gen1 (Type A)	2 x USB 3.2 Gen1 (Type A)
USB (Side Contacts)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)		1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)
USB (Upstream)	1 x USB Type C, 1 x USB 3.2 Gen1 Type B	1 x USB 3.2 Gen1	1 x USB Type C, 1 x USB 3.2 Gen1 Type B
Interfaces	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 1 x HDMI 1.4, 1 x DisplayPort out for DaisyChain (MST)	1 x DisplayPort, 1 x HDMI 1.4, 1 x Dual Link DVI, Daisy Chain (MST)	1 x DisplayPort, 1 x USB Type C (DP alternate mode), 1 x HDMI, 1 x D-SUB, Daisy Chain (MST)
Stand Type	6-in-1	6-in-1	6-in-1
Height adjustment range	150 mm	130 mm	150 mm
Special Features	KVM Switch, RJ 45, LAN 1 Gbit/s, USB Type - C Port Replicator, Power delivery 65 W, AIO Mode	Sensor Keys	USB Type C Port Replicator, Power delivery 65 W, AIO Mode
Data Sheet	TE: Link TS: Link	Link	V141
Product Page	TE: Link TS: Link	Link	Link

P-Line

P-Line Superior Displays are your choice for an uncompromising modern workplace, with a wide range of technical functions and P-Line fittings.

- Frameless In-Plane-Switching (IPS) panels with 100% coverage up to 138% sRGB color space and up to 98% DCI P3 for maximum visual pleasure
- Pre-calibrated for best picture quality
 - High-precision color calibration $\Delta E \leq 2$
 - DICOM compatible greyscale standard preset for clinical review applications
- Ergonomics (6-in-1 stand base): User can tilt, swivel, adjust height and rotate monitor in a wide range to get the optimal posture for long working days. The cable guide and appliance for PC backpack enable a complete workspace solution.
- Built-in sensors: Assist workplace security with presence detection and reduced eyestrain by adjusting settings optimal with Auto Brightness Control (ABC). On top these functions increase energy efficiency
- Audio: Built-in speakers (2x2W), headphone connectors
- USB Type - C Docking: With 65W charging, DP Alternate Mode, KVM functions and 1 Gbit LAN connection
- DisplayView™ software: Monitor configuration by mouse click, release of split-screen and multi-monitor functions. Best UXperience.

A feast for your eyes

Fujitsu Superior Displays (B-Line)

Advanced

			
Features	B32-9 TS UHD	B27-9 TS/TE QHD	B27-9 TS/TE FHD
Size	31.5 in (80 cm)	27 in (68.5 cm)	27 in (68.5 cm)
Aspect Ratio	16:9	16:9	16:9
Native Resolution	3840 x 2160	2560 x 1440	1920 x 1080
USB (Downstream)	2 x USB 3.2 Gen1	2 x USB 3.2 Gen1 (Type A)	2 x USB 3.2 Gen1 (Type A)
USB (Side Contacts)		1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)
USB (Upstream)	1 x USB 3.2 Gen 1 (5 Gbps)	1 x USB 3.2 Gen 1 (5 Gbps)	1 x USB 3.2 Gen 1 (5 Gbps)
Interfaces	1 x DisplayPort 2 x HDMI 2.0	1 x DisplayPort 1 x HDMI 1.4 1 x DVI	1 x DisplayPort 1 x HDMI 1.4 1 x D-SUB
Stand Type	5-in-1	6-in-1	6-in-1
Height adjustment range	130 mm	150 mm	150 mm
Special Features	In-Plane Switching (IPS) technology, high-precision color calibration $\Delta E \leq 2$, low blue light mode, integrated speakers, always available USB (in operating and standby mode)	In-Plane Switching (IPS) technology, high-precision color calibration $\Delta E \leq 2$, 3-coloured Eco status LED, integrated speakers, always available USB (in operating and standby mode)	In-Plane Switching (IPS) technology, high-precision color calibration $\Delta E \leq 2$, 3-coloured Eco status LED, integrated speakers, always available USB (in operating and standby mode)
Audio	2 x 3 W	2 x 2 W	2 x 2 W
Data Sheet	Link	TS: Link TE: Link	TS: Link TE: Link
Product Page	Link	TS: Link TE: Link	TS: Link TE: Link

B-Line

B-Line Displays are designed for best ergonomics and user comfort, as it's the most suitable choice to get robust B-Line displays for 24/7 permanent operation. The huge range of features and applications turn them into the perfect assistant for efficient office work.

- Ergonomics: 6-in-1 wobble-free stand (height adjustment, tilt, swivel, pivot, cable guide), picture over desk (down to 40mm)
- Audio: Built-in speakers and headphone connectors
- Special features: Tactile keys front-side with haptic and sonic feedback, eco Button, multi-color status LED
- DisplayView™ software: Monitor configuration by mouse click, release of split-screen and multi-monitor functions. Best UXperience.

A feast for your eyes

Fujitsu Superior Displays (B-Line)

Advanced

				
Features	B2410 WE/WS	B24-9 TE/TS	B24-9 WE/WS	B24W-7 LED
Size	24.1 in (61.13 cm)	23.8 in (60.5 cm)	24 in (61 cm)	24.1 in (61 cm)
Aspect Ratio	16:10	16:9	16:10	16:10
Native Resolution	1920 x 1200	1920 x 1080	1920 x 1200	1920 x 1200
USB (Downstream)	2 x USB 3.2 Superspeed 5Gbit (USB Type A)	2 x USB 3.2 (Gen1) (Type A)	2 x USB 2.0 (Type A)	2 x USB 2.0 (Type A)
USB (Side Contacts)	1 x USB 3.2 Gen1 (Type A), 1 x USB Type C (15 W + data)			
USB (Upstream)	1 x USB 3.2 Gen 1 Type B	1 x USB 3.2 gen 1 (5 Gbps) Type B	1 x USB 2.0 Type B	1 x USB 2.0 Type B
Interfaces	1 x DisplayPort 1 x HDMI 1.4 1 x DVI-D (HDCP) 1 x D-SUB	1 x DisplayPort 1 x HDMI 1.4 1 x D-SUB	1 x DisplayPort 1 x HDMI 1.4 1 x D-SUB	1 x DisplayPort 1 x DVI-D (HDCP) 1 x D-SUB
Stand Type	6-in-1	6-in-1	6-in-1	4-in-1
Height adjustment range	150 mm	150 mm	130 mm	130 mm
Special Features	Presence sensor with PC security solution, Workplace lightning guide, low blue light mode, color accuracy average Delta E<2, Auto brightness Control (ABC)	In-Plane Switching (IPS) technology, low blue light mode, cable guide, Eco Button for Eco mode and 3-colored Eco status LED	In-Plane Switching (IPS) technology, low blue light mode, cable guide, Eco Button for Eco mode and 3-colored Eco status LED	In-Plane Switching (IPS) technology, pivot, integrated speakers, always available USB
Audio	2 x 2 W	2 x 2 W	2 x 2 W	2 x 1.5 W
Data Sheet	WE: Link WS: Link	TE: Link TS: Link	WE: Link WS: Link	Link
Product Page	WE: Link WS: Link	TE: Link TS: Link	WE: Link WS: Link	Link

B-Line

B-Line Displays are designed for best ergonomics and user comfort, as it's the most suitable choice to get robust displays for 24/7 permanent operation. The huge range of features and applications turn them into the perfect assistant for efficient office work.

- Ergonomics: 6-in-1 wobble-free stand (height adjustment, tilt, swivel, pivot, cable guide), picture over desk (down to 40mm)
- Audio: Built-in speakers and headphone connectors
- Special features: Tactile keys front-side with haptic and sonic feedback, eco Button, multi-color status LED
- DisplayView™ software: Monitor configuration by mouse click, release of split-screen and multi-monitor functions. Best UXperience.

A feast for your eyes

Fujitsu Superior Displays (B-Line)

Advanced



Features	B24-8 TE/TS Pro	B22-8 WE Neo	B22-8 TS Pro	B19-7 LED
Size	23.8 in (60.5 cm)	22 in (55.9 cm)	21.5 in (54.6 cm)	19 in (48.3 cm)
Aspect Ratio	16:9	16:10	16:9	5:4
Native Resolution	1920 x 1080	1680 x 1050	1920 x 1080	1280 x 1024
USB (Downstream)	2 x USB 2.0 Type A	2 x USB 2.0 Type A	2 x USB 2.0 Type A	-
USB (Side Contacts)				
USB (Upstream)	1 x USB 2.0 Type B	1 x USB 2.0 Type B	1 x USB 2.0 Type B	-
Interfaces	1 x HDMI (TS), 1 x DisplayPort (TE) 1 x DVI-D (HDCP) 1 x D-SUB	1 x DisplayPort 1 x DVI-D (HDCP) 1 x D-SUB	1 x DisplayPort 1 x DVI-D (HDCP) 1 x D-SUB	1 x DVI-D (HDCP) 1 x D-SUB
Stand Type	6-in-1	6-in-1	6-in-1	4-in-1
Height adjustment range	150 mm	130 mm	150 mm	130 mm
Special Features	In-Plane Switching (IPS) technology. Pivot, cable guide, integrated, always available USB	Pivot, integrated speakers, Eco button for Eco mode and 3-colored Eco status LED	In-Plane Switching (IPS) technology. Cable guide, pivot, integrated speakers	In-Plane Switching (IPS) technology, pivot, integrated speakers
Audio	2 x 2 W	2 x 1.5 W	2 x 2 W	2 x 1.5 W
Data Sheet	TE: Link TS: Link	Link	Link	Link
Product Page	TE: Link TS: Link	Link	Link	Link

B-Line

B-Line Displays are designed for best ergonomics and user comfort, as it's the most suitable choice to get robust displays for 24/7 permanent operation. The huge range of features and applications turn them into the perfect assistant for efficient office work.

- Ergonomics: 6-in-1 wobble-free stand (height adjustment, tilt, swivel, pivot, cable guide), picture over desk (down to 40mm)
- Audio: Built-in speakers and headphone connectors
- Special features: Tactile keys front-side with haptic and sonic feedback, eco button, multi-color status LED
- DisplayView™ software: Monitor configuration by mouse click, release of split-screen and multi-monitor functions. Best UXperience.

Learn more on FUJITSU Display Offerings:

- [fujitsu.com/GLOBAL](https://www.fujitsu.com/GLOBAL)
- [fujitsu.com/fts/DISPLAYS](https://www.fujitsu.com/fts/DISPLAYS)
- [fujitsu.com/fts/PRODUCT-FINDER](https://www.fujitsu.com/fts/PRODUCT-FINDER)

Our maintenance and Product Support Services:

- [fujitsu.com/fts/servicepositioning](https://www.fujitsu.com/fts/servicepositioning)

A feast for your eyes

Fujitsu Superior Displays (E-Line)

All-round

			
			
Features	E24-9 TOUCH	E24-8 TS Pro	E22-8 TS Pro
Size	23.8 in (60.5 cm)	23.8 in (60.5 cm)	21.5 in (54.6 cm)
Aspect Ratio	16:9	16:9	16:9
Native Resolution	1920 x 1080	1920 x 1080	1920 x 1080
USB (Downstream)	3 x USB 3.2 Gen1 (Type A)	-	-
USB (Side Contacts)	1 x USB 3.2 Gen1 (Type B)	-	-
Interfaces	1 x DisplayPort 1 x HDMI 1 x D-SUB	1 x DisplayPort 1 x DVI-D (HDCP) 1 x D-SUB	1 x DisplayPort 1 x DVI-D (HDCP) 1 x D-SUB
Stand Type	Frame Type Stand	Tilt -5° to 25 °	Tilt -5 ° to 25 °
Special Features	10 point Projected Capacitive Touch (PCT)	IPS technology, eco function	IPS technology, eco function
Data Sheet	Link	Link	Link
Product Page	Link	Link	Link

E-Line

E-Line are entry-level displays that provide everything for everyday office scenarios.

- Good picture thanks to IPS Technology
- 10-finger touch version available
- Energy efficiency: Eco operation mode, eco key and status LED
- Backpack support: for Fujitsu FUTRO Thin Clients and ESPRIMO Q Mini PCs
- Special features: Eco button, integrated speakers

© 2021 Fujitsu Technology Solutions GmbH. All rights reserved. Fujitsu and Fujitsu logo are trademarks of Fujitsu Limited registered in many jurisdictions worldwide. Other product, service and company names mentioned herein may be trademarks of Fujitsu or other companies. This document is current as of the initial date of publication and subject to be changed by Fujitsu without notice. This material is provided for information purposes only and Fujitsu assumes no liability related to its use. We reserve the right to change delivery options or make technical modifications.