BUSCH-JAEGER

NEW



Guard Unit.
ABB-Welcome IP

Functions at a glance

- Display of the video image of the outdoor station. During the conversation a picture of the visitor can be taken and stored in the picture memory.
- Comfortable communication functions.
- Transfer of incoming calls.
- Support for monitoring of outdoor stations or IP cameras.
- Support for enabling all doors or special doors in case of an emergency.
- Wall or table mounting possible (table and wall brackets included in the scope of delivery).
- With hands-free function, volume is adjustable.
- Capacitive display with glass surface (Resolution: 1024 x 600).
- Power supply via Power-over-Ethernet (PoE) 802.3af.
- Alternative power supply 24 Volt DC, 280 mA.
- Alternative power supply via adapter plug 53011PS-03.
- Nennstrom: 280mA (24VDC)
- Protection class (device): IP 30
- Temperature range (device): -40 °C - 55 °C
- Dimensions: (L x W x D): 150 mm x 165 m x 265 m

Order details

Article No.:	H8303-03
Order No.:	2TMA130160W0022
EAN:	6955891811324
Customs tariff number:	85177000
Price group:	23
Price:	1.481,00 EUR plus VAT
Info sheet:	» Download PDF

Downloads

Instruction manual

» Product manual
» Installation and operating instructions

Certificates

» EU-declaration of conformity
» ROHS product declaration