

| Art.-No.  | VE | PG  | EAN                                                                                                  |
|-----------|----|-----|------------------------------------------------------------------------------------------------------|
| 131456008 | 5  | 114 | <br>4 008224 259446 |

Surface mount, earthed socket outlet, 2-fold, prewired, all hinged lids with inscription area, vertical, 16A, 250V~, IP44, BLUE ELECTRIC, grey

| Technical data                                |                             | 131456008 |
|-----------------------------------------------|-----------------------------|-----------|
| Model                                         | Protective contact (SCHUKO) |           |
| Imprint/indication                            | Without imprint             |           |
| Connection type                               | Plug clamp                  |           |
| Colour                                        | Grey                        |           |
| Colour (user defined)                         | grey                        |           |
| Special power supply                          | No special power supply     |           |
| Mounting method                               | Surface mounted (plaster)   |           |
| Type of fastening                             | Mounting with screw         |           |
| Material                                      | Plastic                     |           |
| Material quality                              | Thermoplastic               |           |
| Surface protection                            | Untreated                   |           |
| Surface finishing                             | Glossy                      |           |
| Suitable for degree of protection (IP)        | IP44                        |           |
| Number of units                               | 2                           |           |
| With hinged lid                               | Yes                         |           |
| With child-protection                         | No                          |           |
| Label space/information surface               | Yes                         |           |
| Transparent                                   | No                          |           |
| Lockable                                      | No                          |           |
| Eject-mechanism                               | No                          |           |
| With function lighting                        | No                          |           |
| With orientation lighting                     | No                          |           |
| Over voltage protection                       | No                          |           |
| Fault current protection                      | No                          |           |
| With miniature fuse                           | No                          |           |
| Halogen free                                  | Yes                         |           |
| Rotated central insert                        | No                          |           |
| Nominal current                               | 16A                         |           |
| Nominal voltage                               | 250V                        |           |
| For heavy conditions (in accordance with VDE) | Yes                         |           |

