

DELTA flaeche IP44, AP Dark gray/light gray pushbutton 10 A 250 V,  
66x 75 mm with white window (neutral/ light/bell/door opener)



| Model                             |                                       |
|-----------------------------------|---------------------------------------|
| Product brand name                | DELTA                                 |
| Design of the product             | single pushbutton                     |
| Design of the switching function  | 1 NO contact                          |
| Type of composition               | basic element with complete enclosure |
| Design of the operating mechanism | pushbutton/momentary pushbutton       |
| General technical data            |                                       |
| Printed marking                   | Other                                 |
| Mounting type                     | fixing with screw                     |
| Surface processing                | others                                |
| Material                          | others                                |
| Protection class                  |                                       |
| Protection class IP               | IP44                                  |
| Switching capacity                |                                       |
| Switching capacity current        | 10 A                                  |
| Main circuit                      |                                       |
| Operating voltage / Rated value   | 230 V                                 |

|                                 |      |
|---------------------------------|------|
| Operating current / rated value | 10 A |
|---------------------------------|------|

## Appearance

|            |       |
|------------|-------|
| Appearance | shiny |
| Color      | grey  |

## Product details

|                             |     |
|-----------------------------|-----|
| Product component           |     |
| • Labeling field            | No  |
| • Integrated / Light source | Yes |
| • Signaling contact         | No  |
| Product feature             |     |
| • halogen-free              | Yes |
| • transparent               | No  |

## Number

|                             |   |
|-----------------------------|---|
| Number of actuating rockers | 1 |
|-----------------------------|---|

## Mechanical Design

|                             |                 |
|-----------------------------|-----------------|
| Height                      | 75 mm           |
| Width                       | 66 mm           |
| Depth                       | 54 mm           |
| Mounting type               | surface mounted |
| Material / of the enclosure | plastic         |

## Certificates

|                                 |                                        |                          |
|---------------------------------|----------------------------------------|--------------------------|
| <b>General Product Approval</b> | <b>Declaration of Con-<br/>formity</b> | <b>Test Certificates</b> |
|---------------------------------|----------------------------------------|--------------------------|



ÖVE



VDE



EG-Konf.

[Type Test  
Certificates/Test Report](#)

## Further information

### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TD4701>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TD4701>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TD4701](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TD4701)

### CAX-Online-Generator

<http://www.siemens.com/cax>

### Tender specifications

<http://www.siemens.com/specifications>

