

Reolink-TrackMix-IP-Camera-Specifications		
	Model	Reolink TrackMix
Video & Audio	Image Sensor	1/3"CMOS Sensor
	Video Resolution	UP To: 2560 x 1440 (4.0 Megapixels) at 15 frames/sec
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
	Video Format	H.264,H.265
	Field of View	Horizontal: 96°-38°
		Vertical: 55°-21°
	Zoom Mode	6X hybrid zoom
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 15 Meters (50ft)(LED: 2pcs/850nm)
	Color Night Vision	Spotlight: 1pcs/6500K/450 Lumens
	Audio	Two-way audio
Power	Battery	5100mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel 2
	DC Power	5V/2A
Interface	Power	USB Type-C port
	System	Reset button
	Storage	Micro SD card slot (Max. 128GB)
	Audio	Built-in microphone and speaker
Pan & Tilt	Pan &Tilt	Pan: 355°, Tilt: 0°~90°; (Speed can be set)
	Preset	32
	Auto Tracking	Support
Wi-Fi	Wireless Standard	IEEE 802.11a/b/g/n
	Operating Frequency	2.4GHz/5GHz
	Wireless Security	WPA-PSK/WPA2-PSK
Software Features	Frame Rate	Mainstream: 10fps - 15fps
		Substream: 10fps - 15fps
	Code Rate	Mainstream: 1024Kbps -4096Kbps
		Substream: 64Kbps -512Kbps
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	PIR detection/person detection/vehicle detection/pet detection
	Record Mode	Motion triggered recording
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
Working Environment	Maximum User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
	Work with	Google Assistant, Reolink Cloud
	Operating Temperature	-10°C~+55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
Size & Weight	Waterproof	Support
	Dimension	228.2*147*129mm
	Weight	1.4KG
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/