



6768813525



IP55



**Socket outlet with earthing pin and hinged cover surface-mounted with labelling field, enhanced contact protection, Berker W.1, grey/light grey matt**

#### Technical features

#### Architecture

- 2pole + earth

#### Main electrical features

|               |          |
|---------------|----------|
| Rated current | 16 A     |
| Rated voltage | 250 V AC |

#### Cover, door

- Complete housing

#### Materials

|                       |               |
|-----------------------|---------------|
| Colour of design line | light grey    |
| Material              | thermoplastic |
| Surface appearance    | matt          |

#### Connection

|                          |                          |
|--------------------------|--------------------------|
| Connection terminals     | according to IEC 60884-1 |
| - with plug-in terminals |                          |

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

#### Use

- with labelling field
- enhanced contact protection

#### Safety

|                                                |                          |
|------------------------------------------------|--------------------------|
| Enhanced contact protection (child protection) | according to IEC 60884-1 |
| Enhanced contact protection (child protection) | according to VDE 0620-1  |
| - without enhanced contact protection          |                          |

#### Use conditions

|                               |               |
|-------------------------------|---------------|
| Operating temperature         | -40 ... 30 °C |
| Storage/transport temperature | -50 ... 50 °C |

#### Identification

|                  |            |
|------------------|------------|
| Main design line | Berker W.1 |
|------------------|------------|