

ThinkCentre M75q Tiny **11A40008GE**

Product

ThinkCentre M75q-1 Tiny

Region

WE

Country/Region

Germany

Machine Type

11A4

TopSeller

TopSeller

Processor

AMD Ryzen 3 PRO 3200GE (4C / 4T, 3.3 / 3.8GHz, 2MB L2 / 4MB L3)

Chipset

AMD B300 Chipset

Graphics

Integrated AMD Radeon Vega 8 Graphics

Memory

1x 4GB DDR4-2666

Storage

500GB HDD 7200rpm 2.5"

Optical

None

Speaker

1.5Wx1

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

RTL8822CE 11ac, 2x2 + BT5.0

Optional Rear Ports

1x VGA

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

None

Toolless Chassis Screw

Toolless Chassis Screw

Dust Filter

None

VESA Mount

None

Color

Black

Stand

Stand

Keyboard

USB Traditional Keyboard, Black, German

Mouse

USB Calliope Mouse

Power Supply

65W 88% Adapter

TUV Low Noise

None

Monitor Cable

None

System Management

DASH

Operating System

Windows 10 Home 64, German

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN / UPC / JAN

0194552485375

End of Support

2025-12-12

Announce Date

2019-11-12

Recommended Services**Better**

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36207)

Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26647)



WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<https://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2020. All rights reserved.



Lenovo™

ThinkCentre M75q-1 Tiny Platform Specifications

Product Specifications Reference (PSREF)

Processor	AMD Athlon PRO or Ryzen 3 / 5 PRO series processor						Security features - Security slot (in rear for optional Kensington® MicroSaver® cable) - Smart USB protection, allows keyboard/ mouse only, blocks all storage devices - Power-on password - Administrator password - Hard disk password - Boot sequence control - Boot without keyboard and mouse - Individual USB port disablement - Chassis intrusion switch									
	Processor	Cores / Threads	Frequency Base/Max	L2 / L3 Cache	Memory Support (Up to)	Integrated Graphics										
	Athlon PRO 200GE	2 / 4	3.2 GHz	1 MB / 4MB	DDR4-2666	Radeon Vega 3										
	Athlon PRO 300GE	2 / 4	3.4 GHz	1 MB / 4MB	DDR4-2666	Radeon Vega 3										
	Ryzen 3 PRO 2200GE	4 / 4	3.2 / 3.6 GHz	2 MB / 4MB	DDR4-2933	Radeon Vega 8										
	Ryzen 5 PRO 2400GE	4 / 8	3.2 / 3.8 GHz	2 MB / 4MB	DDR4-2933	Radeon Vega 11										
	Ryzen 3 PRO 3200GE	4 / 4	3.3 / 3.8 GHz	2 MB / 4MB	DDR4-2933	Radeon Vega 8										
Ryzen 5 PRO 3400GE	4 / 8	3.3 / 4.0 GHz	2 MB / 4MB	DDR4-2933	Radeon Vega 11											
Memory	32GB max, DDR4-2666*, two 260-pin SO-DIMM sockets, dual-channel capable * System board supports up to DDR4-2666 memory, and memory may clocks down to DDR4-1866, DDR4-2133 or DDR-2400 for lower capacity of memory controller in processor						Keyboard - Some: Lenovo Traditional Keyboard (USB connector), black - Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black - Some: Lenovo Calliope Mouse (USB connector), black - Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black (only available via special bid models) - Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black									
Disk	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: M.2 SSD (2242 / 2280) / PCIe NVMe, PCIe 3.0 x2 or PCIe 3.0 x4															
Optical	Some: DVD-ROM, 9.0mm high, via USB external ODD box Some: DVD±RW, 9.0mm high, via USB external ODD box						<table><tr><td></td><td>Dimensions (WxDxH)</td><td>Weight (Approx.)</td></tr><tr><td>Tiny only</td><td>7.0" X 7.2" X 1.4" (1.5" with rubber feet) 179mm X 183mm X 34.5mm (37mm with rubber feet)</td><td>2.91 lb (1.32 kg), vary by config</td></tr><tr><td>With VESA mount & ODD box</td><td>7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm</td><td>3.66 lb (1.66 kg), vary by config</td></tr></table>		Dimensions (WxDxH)	Weight (Approx.)	Tiny only	7.0" X 7.2" X 1.4" (1.5" with rubber feet) 179mm X 183mm X 34.5mm (37mm with rubber feet)	2.91 lb (1.32 kg), vary by config	With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config
	Dimensions (WxDxH)	Weight (Approx.)														
Tiny only	7.0" X 7.2" X 1.4" (1.5" with rubber feet) 179mm X 183mm X 34.5mm (37mm with rubber feet)	2.91 lb (1.32 kg), vary by config														
With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config														
Onboard SATA	One SATA 6.0Gb/s connector on system board															
Graphics	AMD Radeon™ Graphics in processor, uses main memory, DirectX® 12, one DisplayPort™, one HDMI, one optional port (VGA, 2nd DP, or 2nd HDMI), supports 3 independent displays (supports maximum of 2 concurrent HDMI/DVI displays when using HDMI port or DP to DVI/HDMI dongles, and Athlon / Athlon PRO only support 2 displays); Max resolution: 4096x2160 (DP)@60Hz; 4096x2160 (HDMI)@30Hz; 1920x1200 (VGA)@60Hz						VESA mount Floor Stand - Optional VESA mount bracket kit, supports VESA 75mm and 100mm - Optional system floor stand for vertical orientation									
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle, or DP to HDMI 1.4 dongle															
Chipset	AMD B300 Chipset						Power supply - Some: 65 watts adapter, autosensing, 88% PSU (not included for TIO models) - Some: 135 watts adapter, autosensing, 88% PSU (not included for TIO models)									
Front ports* (Std.)	one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)						Limited warranty 1-year or 3-year, limited onsite service / service upgrades available									
Rear ports* (Std.)	1x USB 3.1 Gen1, 3x USB 2.0, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI						Preload - Preloaded operating system - Some: Windows® 10 Pro 64-bit - Some: Windows 10 Home 64-bit - Some: Windows 10 IoT Enterprise - Some: Linux Ubuntu									
Rear ports* (Opt.)	Two optional ports: Port 1 for VGA / 2nd DP / 2nd HDMI / serial; Port 2 for serial; * Depending on many factors, actual data transfer speed may be lower than theoretical speed															
Audio support	High Definition (HD) Audio, Realtek ALC222CG / internal speaker (1.5 watt)						Environment ENERGY STAR® 7.1*, EPEAT™ Silver rating* (*Not for non-OS models); ErP Lot 3; RoHS-compliant; TUV low noise verified									
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2						MIL-SPEC test MIL-STD-810H military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)									
Bluetooth	Some: Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter						Accessories For compatible accessories, please go to http://smartfind.lenovo.com									
Ethernet	Gigabit ethernet, Realtek RTL8111EPV-CG, Wake on LAN®															
Manageability	DASH 1.0/1.1															
Security chip	Discrete TPM 2.0, TCG Certified															

Note: The specifications above may not be available in all regions.

Lenovo, April 2020

Lenovo

ThinkCentre M75q Tiny

