

47527204

SCHUKO socket outlet with hinged cover Labelling field, enhanced contact protection, Berker K.5, stainless steel, metal matt finish

Technical features

Architecture

Design	according to DIN 49440

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- with self-closing hinged covers
- Central cover plate

Materials

RAL colour	RAL 9022 - Pearl light grey
Colour of design line	Stainless steel
Colour	stainless steel optics
Colour	stainless steel
Material / workmanship	metal, matt finish
Material	stainless steel
Surface appearance	matt

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with plug-in terminals

Use

- Labelling field
- enhanced contact protection

Safety

Protection index IP	IP44
IK protection code against mecanical impacts	07
Enhanced contact protection (child protection)	according to IEC 60884-1
Enhanced contact protection (child protection)	according to VDE 0620-1

- Enhanced contact protection

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker K.5
Secondary design line(s)	Berker K.5

Instructions

- Labelling field height arranged for 6 mm P-touch strips.

  Specially suited to combinations of several socket outlets if right angle plugs are used.