Product data sheet

Specifications

APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack Marine



SRT192RMBPM

Overview

Lead time	Usually in Stock

Main

Number of rack unit	3U
Battery type	Lead-acid battery
Provided equipment	Installation guide Warranty card

Physical

Colour	Black
Height	13 cm
Width	43.2 cm
Depth	68.27 cm
Net weight	91 kg
Mounting mode	Rack-mounted

Environmental

Ambient air temperature for operation	0…40 °C
Relative humidity	0…95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15…45 °C
Storage Relative Humidity	0…95 % non-condensing
Storage altitude	0.00…15240.00 m

Batteries & Runtime

Device mounting	Stand alone battery stack
Number of battery filled slots	0
Number of battery free slots	0
Number of battery replacement quantity	2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery voltage	192 V
Replacement battery	APCRBC140 SRT192BP2US SRT192RMBPUS SURT10000XLIX710 SURT192XLBP-IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	42 cm
Package 1 Width	100 cm
Package 1 Length	60 cm
Package 1 Weight	105.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace

Recommended replacement(s)