Data Sheet

2 Port Micro PS/2 VGA Cable KVM Switch

Product ID: SV221MICRO

This 2-port Micro KVM switch lets you take command of two PS/2-controlled computers from a single console, without sacrificing any desk space.

A space-saving and cost-effective computer management solution, the compact Micro KVM switch can be hung or tied up out of the way to free up work space, and features ultra-thin cables built on to the switch, leaving zero footprint once installed.

The Micro KVM switch draws power from connected computers and doesn't require an external power source - eliminating the need to position the switch near an available power outlet and saving the space required for a power cable.

Don't let the size fool you! This high quality Micro KVM switch delivers robust display capability with support for resolutions up to 2048x1536 (@60Hz) and supports hot plug-and-play installation for easy deployment.

Designed to ensure a seamlessly dependable operating experience, the 2-port Micro KVM switch is backed by StarTech.com's 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

RoHS Compliant Available

Applications

- Allows control of 2 computers from 1 user console
- Perfect for integrating two different enterprise computer systems

Features

- Automatically switch between 2 computer using the hot key commands
- Dependable 3-year Warranty
- Designed to integrate into your existing IT infrastructure and requires no software to be installed
- Plug n Play support allows users to change computers without any interruptions
- Supports MS Intellimouse (Pro Version), Explorer and Optical Mouse
- Ultra compact design and thin coaxial cables increases the availability and manageability of the server or workstation environment by using only one keyboard, monitor and a mouse

	Warranty	3 Years
Hardware	Audio	Nein
	Einbaufähig	Nein
	KVM-Ports	2
	Mehrfach-Monitor	1
	Mit Kabeln	Ja
	PC-Schnittstelle	PS/2
	PC-Videotyp	VGA
	Reihenschaltung	Nein
Leistung	DVI-Unterstützung	Nein
	Hot-Key Selection	Nein
	IP-Steuerung	Nein
	Max. Analogauflösungen	2048x1536
	Max. Anzahl von Benutzern	1
Steckverbinder	Hostanschlüsse	2 - VGA (15-polig, High Density D-Sub) Stecker
		4 - PS/2 (6-polig, Mini-DIN) Stecker
	Konsolen-Schnittstelle(n)	1 - VGA (15-polig, High Density D-Sub) Buchse
		2 - PS/2 (6-polig, Mini-DIN) Buchse
Anzeiger	LED-Anzeiger	2 - CPU A/B Selection indicators
Physische Eigenschaften	Gehäusetyp	Kunststoff
	Kabellänge	6 ft [1.8 m]
	Produktbreite	0.5 in [11.8 mm]
	Produktgewicht	13.4 oz [380 g]
	Produkthöhe	1.1 in [27.6 mm]
	Produktlänge	3 in [75.6 mm]
Verpackungsinformationen	Versandgewicht (Verpackung)	1 lb [0.5 kg]
Verpackungsinhalt	Im Paket enthalten	1 - 2 Port Micro KVM on Cable
		1 - Hot Key Reference Strip
		1 - Instructional Manual

Product appearance and specifications are subject to change without notice.