



## Thunderbolt 3 Docking Station

No.: 43903

Connect dual 4K60 displays and peripherals over a single cable

### Description

- Connects an HDMI and Thunderbolt 3 display, USB peripherals and power over a single cable
- Supports Ultra HD 4K 60Hz for both displays and even 5K at the Thunderbolt 3 port
- Integrated 5 port USB 3.1 Gen 1 / USB 3.0 SuperSpeed Hub
- USB Power Delivery capable up to 60W
- 2 year warranty

The Lindy Thunderbolt 3 Docking Station is a powerful and multifunctional solution for connecting notebooks and Macbooks to a range of interfaces including dual displays, using a single cable.

Only Thunderbolt 3 with its incredible bandwidth of 40 Gbps allows two 4K 60Hz displays simultaneously or even one 5K 60Hz display while outputting video and audio signal at the same time. It is an essential tool for professional creatives to streamline their workflows, no matter whether for photo and video editing, rendering in real-time, 3D graphics, virtual reality or computer-aided design. Thunderbolt 3 helps to avoid bottlenecks for demanding work in general.

Featuring all the interfaces needed for a standard workstation, the Lindy Thunderbolt 3 Docking Station uses a single cable to connect to a notebook or Macbook to simultaneously provide dual monitor capabilities at 4K60Hz, Power, Gigabit Ethernet, an SD card reader, Audio and a USB 3.1 SuperSpeed hub. The Docking Station also allows powering of the connected devices and charging of your notebook/Macbook through the Power Delivery port at the same time with 60 Watt.

### Technical details

#### Specifications

- Interface: Thunderbolt 3 USB Type C to 5 x USB Type A / 1 x Thunderbolt 3 USB Type C / 1 x HDMI / 1 x RJ45 / 1 x SD card / 3.5mm Audio
- Interface Standard:
  - Thunderbolt 3
  - USB 3.1 Gen 1 / 3.0
  - HDMI 2.0
  - Gigabit LAN
  - SD 3.0
  - 3.5mm Audio
- Supported Bandwidth: 40 Gbps, 10/100/1000 Mbps
- Maximum Input Resolution: 4096x2160 / 3840x2160@60Hz, 5120x2880@60Hz
- Maximum Output Resolution:
  - 4096x2160 / 3840x2160@60Hz [simultaneous use]
  - 5120x2880@60Hz [one display only]

- Chipset:
  - Intel Alpine Ridge 4C
  - Parade PS176 (HDMI)
  - TI TPS65983A (PD)
  - Fresco FL1100 (USB Hub)
  - Intel i210 (LAN)
- Compatibility: Thunderbolt 3 USB Type C equipped computers
- Power Delivery: PD 2.0 up to 60W (20V 3A)
- HDCP Support: HDCP 2.2
- Supported Audio: Supports audio 2.1 channel via 4 segment 3.5mm jack
- Separate Audio Ports: -
- Special Features: Supports Battery Charging 1.2 (1 Port)

#### Connectors

- Inputs: 1 x Thunderbolt 3 USB Type C (Male)
- Outputs:
  - 5 x USB Type A (Female)
  - 1 x Thunderbolt 3 USB Type C (Female)
  - 1 x RJ45 (Female), 1 x HDMI (Female)
- Power: 5.5/2.5mm DC socket

#### Physical Properties

- Dimensions WxDxH: 155x85x23mm (6.1x3.35x0.91in)
- Housing Material: Aluminium & plastic
- Net Weight: 0.452kg (1lb)
- Operating Temperature: 0° - 40°C (32°F - 104°F)
- Storage Temperature: -20°C - 70°C (-4°F - 158°F)
- Humidity: 0 - 90% RH (non-condensing)
- Power Requirements: 20VDC 6.75A
- Colour: Silver & black

#### Miscellaneous

- Packaging Type: Carton Box
- Packaging Dimensions: 295x147x90mm (11.61x5.79x3.54in)
- Gross Weight: 1.51kg (3.33lb)
- Warranty (Years): 2
- Certificated: CE, FCC, REACH & RoHS

#### Package Contents

- Thunderbolt 3 Docking Station
- 0.4m Thunderbolt 3 cable (USB Type C Male to Male)
- External Power Supply with DC connector
- Power Cable (UK or Schuko) with IEC C5 connector
- Lindy Manual

#### Purchasing information

- No.: 43903
- EAN: 4002888439039